

REXW Series LED

Construction:

- Steel housing and chassis
- Frameless white textured polycarbonate lens

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Mounting - See notes below dimensions
- Horizontal or vertical mounting
- ADA compliant
- Optional battery backup
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

REXW-315	REXW-326	REXW-415	REXW-426
Height - 15"	Height - 26"	Height - 15"	Height - 26"
Width - 3"	Width - 3"	Width - 4.25"	Width - 4.25"
Depth - 4"	Depth - 4"	Depth - 4"	Depth - 4"

Mounts to 2 x 4 box/opening oriented to match fixture's linear dimension

Mounts to standard J box



ORDERING INFORMATION

Example: REXW-326-LED-U-21W-4-T6-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
REXW-315-LED REXW-415-LED		U 120- 277v	11w LED / 1175lm (106 lm per watt)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black T6 Pewter W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel	WTP White Textured Polycarbonate	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) Battery Backup Options (415 & 426 Series only) BB10 10 Watts (1170lm) for 90-Minutes
REXW-326-LED REXW-426-LED			21w LED / 2450lm (117 lm per watt)				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

