

RHCH-LED

Construction:

- Steel housing and chassis
- Diffuser is .125" thick white smooth acrylic
- Optional alabaster acrylic is .125" thick

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Canopy mounts to J-Box with integral safety cable
- Custom mounting heights available
- Single stem suspension with 45-degree swivel
- Optional battery backup
- Optional bottom lens is white smooth acrylic
- Down Light - Consult Factory
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

RHCH-22

Height - 22"
Width - 10"
OAH - 44"

RHCH-30

Height - 30"
Width - 10"
OAH - 60"

ORDERING INFORMATION

Example: RHCH-22-LED-U-72W-3-Z1-BAA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
RHCH-22-LED		U 120 - 277	72w LED / 8000lm (111 lm per watt)	2 3000K 4 4000K	B1 Satin Black Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster Optional Bottom Lens (see Price List) WBL White Bottom Lens	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) (Suspension Systems-See Notes) IS45 -Single Stem 45 degree swivel 4S Four Stem 1S154AC - Single Stem w/Aircraft Cable 4AC__ - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes
RHCH-30-LED			84w LED / 9800lm (117 lm per watt)	Optional 3 3500K	Optional (see Price List) W2 Gloss White W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige P2 Brushed Alum P9 Brushed Nickel		



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 /661-257-0286 • fax 800-323-2346 /661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

