

WALL

CEILING

PENDANT

OUTDOOR

| | |
|-----------|--|
| Type: | |
| Job Name: | |



Construction:

- Spun Steel Side cover
- Acrylic lens

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Keyhole slots for standard J-box
- UL and CUL listed **DAMP** location
- Field Adjustable Aircraft Cable and SO Cord
- LED Components
 - Replaceable Module
 - CRI > 80, Optional CR > 90
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

RKOH-24

- Fixture Height - 4.5"
- Diameter - 24"
- Overall Height - 24"



Example: RKOH-24-LED-U-36W-4-B1-WFA-3AC-24OAH

| Model | Cage | Voltage | Lamping | Kelvin | Finish | Diffuser | Options |
|----------------|------|-------------------|-------------------------------|---|---|----------------------------------|--|
| RKOH-24 | | U 120-277V | 36w LED / 4,000 lumens | 2 3000K 4 4000K Optional 3 3500K | B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 Yolk White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige Optional (See Price List) M17 Brass Powder | WFA White Frosted Acrylic | DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) (Suspension Systems) Please list Over All Height 3AC -(3) Aircraft Cable 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes |



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

