

SAPP-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" white textured polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED

Notes:

- Mounts to 3" round pole – fitter included
- Fixture dimensions excluded fitter
- See supplemental spec sheet on website for pole options
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SAPP-15-LED

Height - 15"
Width - 8 1/4"
Depth - 8 1/4"

WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: SAPP-15-LED-U-36W-3-B1-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
SAPP-15-LED		U 120 - 277	36w LED / 4000lm (111 lm per watt) 42w LED / 4900lm (117 lm per watt) Socket Base: (Lamp by Others) E26 Medium Base (NL) E39 Moquil Base (NL)	2 3000K 3 3500K 4 4000K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (See Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	Pole Options (see supplemental spec sheet on website and price list)



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

