

SCAW-LED

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



SCAW-10

Height - 10"
Width - 7"
Depth - 4½"

SCAW-13

Height - 12 ½"
Width - 9"
Depth - 5"

SCAW-18

Height - 18"
Width - 13"
Depth - 6 ½"

WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: **SCAW-13-LED-U-13W-4-B1-WTP**

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
SCAW-10-LED		U 120 - 277	13w LED / 1,484 lumens (114 lm per watt)	2 3000K 4 4000K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze	WTP White Textured Polycarbonate Optional Lens Material (See Price List)	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
SCAW-13-LED			13w LED / 1,484 lumens (114 lm per watt)	Optional 3 3500K	Optional (See Price List)	AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	16 Bottom Lens 21 Photocell - <i>See Notes</i> - 01 120 volt - 02 277 volt
SCAW-18-LED			18w LED / 2,000 lumens (111 lm per watt)		W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass		Battery Backup Options (SCAW 18 Only) BB10 10 Watts (1170lm) for 90-Minutes
			21w LED / 2,450 lumens (111 lm per watt)				



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

