

Construction:

- Steel housing and chassis
- Diffuser is .080" thick white textured polycarbonate or optional white smooth polycarbonate
- Optional alabaster lenses are .080" thick acrylic

Lamps:

- Lamps **INCLUDED**

Notes:

- Center lockup – hardware included
- Custom cage styles available
- Dimming ballast may be limited with some lamps
- Closed top eliminates upward light pollution
- Optional battery backup
- Optional photocell (option 21) – specify voltage
- UL and CUL listed **WET** location

Type:	
Job Name:	



SDGW-13	SDGW-13	SDGW-18
Height - 10"	Height - 12 1/2"	Height - 18"
Width - 7"	Width - 9"	Width - 13"
Depth - 4 1/2"	Depth - 5"	Depth - 6 1/2"



WALL

CEILING

PENDANT

OUTDOOR

ORDERING INFORMATION

Example: SDGW-15-A-2Q26-3-B1-WTP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
SDGW-10		1 120v NPF (Mag) A 120v NPF (Elec) U 277v HPF (Elec)	1P13 (1) 13w Mag 2P13 (2) 13w Mag 1Q13 (1) 13w Elec 1Q18 (1) 18w Elec 2Q18 (2) 18w Elec 1Q26 (1) 26w Elec	2 2700K 3 3500K 4 4100K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (See Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	WTP White Textured Polycarbonate Optional Lens Material (See Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster WSP White Smooth Polycarbonate	DIM10 - Mark 10 Dimming Ballast DIM7 - Mark 7 Dimming Ballast 01 120v 02 277v 16 Bottom Lens 21 Photocell - See Notes -01 120 volt -02 277 volt (BB option - 18" size only) (2Q26, 1T32 OR 1T42 only) BB - Battery Backup CBB - Cold Weather BB 01 120v 02 277v 06 650 Lumen (nominal) 12 1250 Lumen (nominal)
SDGW-13			2Q26 (2) 26w Elec 1T32 (1) 32w Elec 1T42 (1) 42w Elec				
SDGW-18			2Q26 (2) 26w Elec 1T32 (1) 32w Elec 2T32 (2) 32w Elec 1T42 (1) 42w Elec 2T42 (2) 42w Elec				



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

