

SDWW-LED

Construction:

- Steel housing and chassis
- Diffuser is white textured or clear textured polycarbonate

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup – hardware included
- Optional photocell (21)
- Optional J-Box with knockouts for surface mount conduit - increases fixture depth to 4"
- ADA Compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

| | |
|-----------|--|
| Type: | |
| Job Name: | |



WALL

CEILING

PENDANT

OUTDOOR

SDWW-7-LED

Height - 6 3/4"
Width - 8 1/2"
Depth - 2 1/4"

ORDERING INFORMATION

Example: SDWW-7-LED-U-7W-3-B1-WTP

| | | | | | | | |
|--|--|--|--|--|--|--|--|
| | | | | | | | |
|--|--|--|--|--|--|--|--|

| Model | Cage | Voltage | Lamping | Kelvin | Finish | Diffuser | Options |
|-------------------|------|--------------------|--|---|--|---|--|
| SDWW-7-LED | | U 120 - 277 | 7w LED / 800lm (114 lm per watt) | 2 3000K 4 4000K Optional 3 3500K | B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (See Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige | WTP White Textured Polycarbonate Optional Lens Material (See Price List) CTP Clear Textured Polycarbonate | DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) 21 Photocell - See Notes -01 120 volt -02 277 volt 39 J-Box with Knockouts 42 All Aluminum Construction |



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

