

SNOC-LED

Type:	
Job Name:	

Construction:

- Aluminum Chassis
- Diffuser is extruded white smooth acrylic

Light Source:

- LED
- Dimming to 10% **Included**

Notes:

- Mounts standard "J-Box", hardware included
- Bottom of fixture is open
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components



SNOC - 11 - 18 - 24 - 36 - 48
 Height - 11" - 18" - 24" - 36" - 48"
 Diameter - 6"



ORDERING INFORMATION

Example: SNOC-11-LED-01J-4-T6-WSA

SNOC

Size	LED					Kelvin	Cage	Finish	Diffuser	Options
		Watts	Source Lumens	Dimming	Energy Star	2 3000K 4 4000K		B1 Satin Black B2 Text Black Z1 Satin Bronze Z3 Text Bronze W1 York White W2 Gloss White T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) 90CRI Consult Factory
11-LED	01J	23	2220	0-10v	NO	Optional 3 3500K				
18-LED	01J	23	2220	0-10v	NO					
24-LED	01J	23	2220	0-10v	NO					
36-LED	01J	23	2220	0-10v	NO					
48-LED	01J	23	2220	0-10v	NO					
							Optional (See Price List) M17 Brass Powder M16 Antique Brass			



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

