

THOW-LED

Construction:

- Steel housing and aluminum chassis
- Diffuser is .10" thick extruded white acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup - hardware included
- Open top and bottom
- Horizontal or vertical mounting
- Optional battery backup
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components
- **For WET listed version see MANW Series**

Type:	
Job Name:	



WALL
CEILING
PENDANT
OUTDOOR

THOW-16-LED

Height - 16"
Width - 7 1/8"
Depth - 4"

THOW-24-LED

Height - 24"
Width - 7 1/8"
Depth - 4"



ORDERING INFORMATION

Example: THOW-16-LED-U-21W-3-B1-WSA

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
THOW-16-LED		U 120-277v	14w LED / 1600lm (114 lm per watt) 21w LED / 2450lm (117 lm per watt)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W1 Yolk W2 Gloss White P0 Polished Brass* P1 Chrome* P2 Brushed Alum	WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
THOW-24-LED			18w LED / 2000lm (111 lm per watt) 21w LED / 2450lm (117 lm per watt)		Optional Finishes (see Price List) M13 Anod Silver T4 Shimmer Gray T6 Pewter W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze		Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes

* Interior Use Only



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

