

VEGC-LED

Construction:

- Steel pan with stamped steel motif accent band
- Diffuser is frost smooth glass or optional white acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Canopy mounts to standard J-Box
- Optional battery backup
- UL and CUL listed DAMP location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

VEGC-15

Height - 8 1/4"

Diameter - 15 1/4"



ORDERING INFORMATION

Example: VEGC-15-LED-U-20W-4-Z3-FSG

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
VEGC-15-LED		U 120 - 277 1 120 Volt	20w LED / 2,325 lumens (116 lm per watt) Socket Base: (Lamp by Others) E26 Medium Base (NL) * Battery Backup not available	2 3000K 4 4000K Optional 3 3500	W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional (see Price List) W1 Yolk W3 Text White B1 Satin Black B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass	FSG Frosted Smooth Glass Optional Lens Material (see Price List) WSA White Smooth Acrylic	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) OCCHFA Concealed Occupancy Sensor <i>See Sensor Resource Sheet</i> Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

