

Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic

Lamps:

- Lamps **INCLUDED** except on linear lamp fixtures

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Dimming ballast may be limited with some lamps
- Battery backup available in the 36" and 48" only
- UL and CUL listed **DAMP** location

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

VTWV-24	VTWV-36	VTWV-48
Height - 4 1/2"	Height - 4 1/2"	Height - 4 1/2"
Depth - 4 1/4"	Depth - 4 1/4"	Depth - 4 1/4"
Length - 24"	Length - 36"	Length - 48"

ORDERING INFORMATION

Example: VTWV-36-A-2F25-NL-W2-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
VTWV-24		A 120v NPF (Elec) U 277v HPF (Elec)	1F17 (1) 17w T8 NL 2F17 (2) 17w T8 NL 1F24 (1) 24w T5HO NL 2F24 (2) 24w T5HO NL	2 2700K 3 3500K 4 4100K NL	W2 Gloss White	WSA White Smooth Acrylic Optional Lens Material (see Price List) CPA Clear Prismatic Acrylic	
VTWV-36			1F25 (1) 25w T8 NL 2F25 (2) 25w T8 NL 1F39 (1) 39w T5HO NL 2F39 (2) 39w T5HO NL				
VTWV-48			1F32 (1) 32w T8 NL 2F32 (2) 32w T8 NL 1F54 (1) 54w T5HO NL 2F54 (2) 54w T5HO NL				BB option - See Notes /36 & 48 only BB - Battery Backup 01 120v 02 277v 05 500 Lumen (nominal) 07 700 Lumen (nominal) 14 1400 Lumen (nominal)



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

