

# VTWV-LED

## Construction:

- Steel chassis and end caps
- Diffuser is white smooth acrylic or optional clear prismatic acrylic
- clear prismatic acrylic

## Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

## Notes:

- Mounts to standard J-Box with slotted anchor holes
- Optional battery backup (36" or 48" only)
- UL and CUL listed **DAMP** location
- LED Components
  - Replaceable Module
  - CRI > 80
  - Universal 120/277 volt standard
  - 5-Year Warranty on LED Components

Type:	
Job Name:	



<b>VTWV-24-LED</b>	<b>VTWV-36-LED</b>	<b>VTWV-48-LED</b>
Height - 4 1/4"	Height - 4 1/4"	Height - 4 1/4"
Depth - 4 1/4"	Depth - 4 1/4"	Depth - 4 1/4"
Length - 24"	Length - 36"	Length - 48"

WALL  
CEILING  
PENDANT  
OUTDOOR

## ORDERING INFORMATION

Example: VTWV-36-LED-U-32W-4-W2-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
<b>VTWV-24-LED</b>		U 120 - 277	<b>21w</b> LED / 2450lm (117 lm per watt)	2 3000K 4 4000K	W2 Gloss White	WSA White Smooth Acrylic	<b>DIM</b> LED dimming driver (0 - 10v) Dimming to 10% ( <b>Included</b> )
<b>VTWV-36-LED</b>			<b>32w</b> LED / 3675lm (117 lm per watt)	<b>Optional</b> 3 3500K		<b>Optional Lens Material</b> (see Price List) <b>CPA</b> Clear Prismatic Acrylic	
<b>VTWV-48-LED</b>			<b>42w</b> LED / 4900lm (117 lm per watt)				

**Battery Backup Options**  
**BB10** 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355  
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201  
 East Coast Sales: 866-350-0991 • fax 866-490-5754  
 www.lightwayind.com • sales@lightwayind.com

