

WPNW-LED

Construction:

- Cast aluminum housing
- Clear smooth polycarbonate lens

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Surface mounted Backbox allows for both standard J-Box and surface ran conduit
- Optional battery backup available
- Optional Photocell (-21); specify voltage
- Dark Sky compliant
- UL and CUL listed **WET** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Integral Power Supply
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL

CEILING

PENDANT

OUTDOOR

WPNW-6

Height - 5 3/4 "
Width - 11"
Depth
Standard - 8 1/2"

WPNW-8

Height - 7 1/2 "
Width - 15 1/2"
Depth
Standard - 10 1/4"
Deep Box - 11"



ORDERING INFORMATION

Example: WPNW-6-LED-U-18W-3-Z3-CSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
WPNW-6-LED		U 120/277v	14w LED / 1600lm (114 lm per watt)	2 3000K 4 4000K	Z99 Bronze	CSP Clear Smooth Poly	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)
			18w LED / 2000lm (111 lm per watt)	Optional 3 3500K			
WPNW-8-LED			21w LED / 2450lm (116 lm per watt)				21 Photocell - Specify voltage 01 - 120 volt 02 - 277 volt
			30w LED / 3600lm (120 lm per watt)				
			36w LED / 4000lm (111 lm per watt)				
							Battery Backup Options BB10 10 Watts (1170lm) for 90-Minutes



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

