

WWXH-LED

Type:	
Job Name:	

Construction:

- Steel construction
- Diffuser is white smooth acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**
- Medium Base Socket (Lamp NOT included)

Notes:

- Canopy mounts to standard "J-Box"
- Custom mounting heights available
- Single ridge 15 degree swivel stem standard (1S15)
Optional cord or cable mounting, see options
- Optional battery backup, battery mounted in oversized canopy. Not available with E26 lamp
- UL and CUL listed **DAMP** location
- 5-Year Warranty on LED Components



WWXH 12 - 14 - 16 - 18 - 20
Height: 12" 14" 16" 18" 20"
Diameter: 12" 14" 16" 18" 20"
OAH: 24" 24" 24" 24" 36"



ORDERING INFORMATION

Example: WWXH-12-LED-A-1E26-NL-Z1-WSA-1S15-24OAH

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options	
WWXH-12-LED		A- 120 volt	1E26 Medium Base Socket (Lamp NOT included) <i>(All Sizes)</i>	NL	B1 Satin Black B2 Text Black M13 Anod Silver T4 Shimmer Gray T6 Pewter W1 Yolk W2 Gloss White W3 Text White W13 Pearl Beige Z1 Satin Bronze Z3 Text Bronze	WSA White Smooth Acrylic	(Suspension Systems) Please list Over All Height 1S15 - Single 15° Swivel Stem (Standard) 1S45 - Single 45° Swivel Stem WSJ - White "SJ" Cord BSJ - Black "SJ" Cord 1AC - Aircraft Cable w/SJ cord WSJ - White "SJ" Cord BSJ - Black "SJ" Cord DIM LED dimming driver (0 - 10v) Dimming to 10% (Included) ES Energy Star Consult Factory 90CRI Consult Factory Battery Backup Options (Available with 0-10v only) BB10 10 Watts (1170lm) for 90-Minutes	
WWXH-14-LED		U 120 - 277	28w LED / 3,200 lumens (114 lm per watt) <i>(All Sizes)</i>	2 3000K 4 4000K	Optional 3 3500K			Optional (See Price List)
WWXH-16-LED			36w LED / 4,000 lumens (111 lm per watt) <i>(WWXH-16" - 18" - 20")</i>					
WWXH-18-LED			42w LED / 4,900 lumens (116 lm per watt) <i>(WWXH-18" - 20")</i>					
WWXH-20-LED								P2 Brushed Alum P9 Brushed Nickel M16 Antique Brass



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

