

XLSW-LED

Construction:

- Aluminum chassis with laser cut housing
- Diffuser is .060" thick white smooth or textured polycarbonate or optional amber, beige or opal alabaster acrylic

Light Source:

- LED
- Dimming (0 - 10v) to 10% **Included**

Notes:

- Center lockup - hardware included
- Custom cage styles available
- ADA compliant
- UL and CUL listed **DAMP** location
- LED Components
 - Replaceable Module
 - CRI > 80
 - Dimming (10% or 1%)
 - Universal 120/277 volt standard
 - 5-Year Warranty on LED Components

Type:	
Job Name:	



WALL
CEILING
PENDANT
OUTDOOR

XLSW-18-LED

Height - 18"
Width - 6 1/2"
Depth - 4"

ORDERING INFORMATION

Example: XLSW-18-LED-U-21W-3-M13-WSP

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
XLSW-18-LED		U 120 - 277	21w LED / 2450lm (117 lm per watt)	2 3000K 4 4000K Optional 3 3500K	B1 Satin Black W2 Gloss White Z1 Satin Bronze Z3 Text Bronze Optional Finishes (see Price List) W1 Yolk W3 Text White B2 Text Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige M16 Antique Brass P9 Brushed Nickel	WSP White Smooth Polycarbonate WTP White Textured Polycarbonate Optional Lens Material (see Price List) AHA Amber Honey Alabaster BAA Beige Alabaster OAA Opal Alabaster	DIM LED dimming driver (0 - 10v) Dimming to 10% (Included)



28435 Industry Drive., Valencia, California 91355
West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
East Coast Sales: 866-350-0991 • fax 866-490-5754
www.lightwayind.com • sales@lightwayind.com

