

Construction:

- Steel chassis and front shield
- Top and bottom diffuser is white smooth acrylic

Lamps:

- Lamps **INCLUDED** except on linear lamp fixtures

Notes:

- Mounts to standard J-Box with slotted anchor holes
- Dimming ballast may be limited with some lamps
- Optional perforated steel top and/or bottom diffuser
- Optional solid top to eliminate up light
- ADA compliant
- UL and CUL listed **DAMP** location

Type:	
Job Name:	



YRBV-18	YRBV-24
Height - 6"	Height - 6"
Depth - 4"	Depth - 4"
Length - 18"	Length - 24"



WALL
CEILING
PENDANT
OUTDOOR

ORDERING INFORMATION

Example: YRBV-24-U-2F24-NL-W1-WSA

--	--	--	--	--	--	--	--

Model	Cage	Voltage	Lamping	Kelvin	Finish	Diffuser	Options
YRBV-18		A 120v NPF (Elec) U 277v HPF (Elec)	2Q13 (2) 13w Elec 2Q18 (2) 18w Elec 2Q26 (2) 26w Elec	2 2700K 3 3500K 4 4100K	W1 Yolk W2 Gloss White Z1 Bronze	WSA White Smooth Acrylic	(Dimming option - See Notes) DIM10 - Mark 10 Dimming Ballast DIM7 - Mark 7 Dimming Ballast 01 120v 02 277v PT Perforated Steel Top PB Perforated steel Bottom ST Solid Top (No Up Light)
YRBV-24		UPS - Program Start	2F17 (2) 17w T8 NL 2F24 (2) 24w T5H0 NL	NL	Optional (see Price List) W3 Text White B1 Satin Black T4 Shimmer Gray M13 Anod Silver T6 Pewter W13 Pearl Beige		



28435 Industry Drive., Valencia, California 91355
 West Coast Sales: 800-325-4448 / 661-257-0286 • fax 800-323-2346 / 661-257-0201
 East Coast Sales: 866-350-0991 • fax 866-490-5754
 www.lightwayind.com • sales@lightwayind.com

