



DHDVR24-B4-V2

24 CHANNEL 4K DVR (CVI / TVI / AHD / CVBS / IP)



















Key Features:

- 24 channel recording (16 channel BNC + 8 channel 8MP IP)
- 5 IN 1 (CVI / TVI / AHD / ANALOGUE / IP)
- P2P (no port forwarding required) Apple app/Android app/Windows PC/Apple Mac PC
- 4K(1~7fps), 5MP(1~12fps), 4MP/3MP@15fps, 1080P/720P@25fps
- 8MP IP realtime recording
- ONVIF 2.4 compatible
- IP spot via network (no convertor required)
- 16 channel playback at the same time
- Max 24 channels IP camera inputs, each channel up to 8MP, Max 48Mbps Incoming Bandwidth
- PTZ control over 1 co-ax cable (mouse control on DVR area zoom & scroll zoom)
- Instant playback on one channel when others are on live viewing
- Smart search & email notification (snapshot)
- Intelligent feature: Facial & Tripwire detection (BNC channel only)
- Backup footage by video clip while viewing playback

SPECIFICATIONS

Model Number DHDVR24-B4-V2

DVR Capacity Recording Ability LINUX Resentation Syllifen Channels **Playback Ability** 8MP646hd Audio 12 FPS24 channel (16 k BNC +C8+x6P)12 FPS EMODIT 5 IN 1 15 FPS16 channel CVI/TVI/AHD/C@BS FPS **Standard** 4MP-N IΡ 25 FPS8 channel (up to 8 Megatri@e21FFPS 1080P 25 FPS 4CH @ 25 FPS 960H 25 FPS 4CH @ 25 FPS (continued)

| Analog Camero | a Inpu | t | 16 Channel, BNC |
|-----------------|-------------------------|----------|---|
| HDCVI Camera | | | 4K@7fps, 6MP@10fps, 5MP@12fps, 4MP@15fps, 1080P/720P@25fps |
| AHD Camera | | | 1080P/720P@25fps |
| TVI Camera | | | 5MP@12fps, 4MP@15fps, 1080P/720P@25fps |
| CVBS Camera | | | PAL/NTSC |
| IP Camera Inpu | υt | | 8 Channel, each channel up to 8MP(4K@7fps, 6MP@10fps, 5MP@12fps) |
| Audio In/Out | | | 1/1, RCA |
| Two-way Talk | | | Reuse audio in/out, RCA |
| Display | | | |
| Interface | | | 1 HDMI, 1 VGA |
| Resolution | | HDMI | 3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720, 1024×768 |
| | | VGA | 1920×1080, 1280×1024, 1280×720, 1024×768 |
| Display Split | | | 1/4/8/9/16/25 |
| OSD | | | Camera title, Time, Video loss, Camera lock, |
| | | | Motion detection, Recording |
| Recording | | | |
| Video/Audio C | ompre | ession | H.264+/H.264 |
| Resolution | | | 4K, 5MP, 4MP, 3MP, 1080P, 720P, 960H, D1, CIF, QCIF |
| Record Rate | Record Rate Main Stream | | 4K(7fps), 5MP(12fps), 4/3MP(15fps) 1080P/720P/960H/D1/CIF/QCIF (25fps) |
| | Extro | a Stream | 960H(1~15fps), D1/CIF/QCIF(1~25fps) |
| Bit Rate | | | 1Kbps ~ 6144Kbps Per Channel |
| Record Mode | | | Manual, Schedule (Regular, Continuous), MD (Video detection: |
| | | | Motion Detection, Video Loss, Tampering), Alarm, Stop |
| Record Interval | | | 1~60 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec |
| Video Detectio | n | | |
| Trigger Events | | | Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, |
| | | | Buzzer and Screen Tips |
| Video Detectio | n | | Motion Detection, MD Zones: 396 (22 × 18), Video Loss, |
| | | | Tampering and Diagnosis |
| Playback & Bad | ckup | | |
| Sync Playback | | | 1/4/9/16 |
| Search Mode | | | Time/Date, MD & Exact search (accurate to second) |
| | | | |

(continued)

| Playl | oack Functions | Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File, | | | | |
|-------|-----------------------------|---|--|--|--|--|
| | | Previous File, Next Camera, Previous Camera, Full Screen, Repeat, | | | | |
| | | Shuffle, Backup Se | Shuffle, Backup Selection, Digital Zoom | | | |
| Back | cup Mode | USB Device/Netw | USB Device/Network | | | |
| Netw | vork | | | | | |
| Inter | face | 1 RJ-45 port (1000 | 1 RJ-45 port (1000M) | | | |
| Netw | ork Functions | HTTP, TCP/IP, IPv4/ | HTTP, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP | | | |
| | | Filter, PPPoE,DDNS | Filter, PPPoE,DDNS, FTP, Alarm Server, P2P,IP Search | | | |
| Max | User Access | 128 users | 128 users | | | |
| Sma | rt Phone | iPhone, iPad, And | iPhone, iPad, Android Phone | | | |
| Inter | operability | ONVIF 2.42, CGI C | ONVIF 2.42, CGI Conformant | | | |
| Store | ige | | | | | |
| Inter | nal HDD | 2 SATA port, up to | 2 SATA port, up to 6TB capacity for each disk | | | |
| Auxi | liary Interface | | | | | |
| USB I | nterface | 2 ports(1 Rear), 1 | 2 ports(1 Rear), 1 USB 3.0 & 1 USB 2.0 | | | |
| RS48 | 5 | 1 port, For PTZ Cor | 1 port, For PTZ Control | | | |
| Gen | eral | | | | | |
| Powe | er Supply | DC12V/5A | DC12V/5A | | | |
| Powe | er Consumption | <15W (without HD | <15W (without HDD) | | | |
| Work | king Environment | -10°C ~+55°C / 0% | -10°C ~+55°C / 0%~90%RH | | | |
| Dime | ensions | Compact 1U, 375 | Compact 1U, 375mm(W)×285mm(D)×55mm(H) | | | |
| Weig | Weight 2.35 KG(without HDD) | | | | | |
| DVR | Capacity | | | | | |
| Reso | lution - BNC Channels | Recording Ability | Playback Ability | | | |
| 8MP | (4K) | 7 FPS | 8CH @ 7 FPS | | | |
| 5MP | | 12 FPS | 8CH @ 12 FPS | | | |
| 4MP | | 15 FPS | 8CH @ 15 FPS | | | |
| 4MP- | N | 25 FPS | 8CH @ 15 FPS | | | |
| 1080 | Р | 25 FPS | 8CH @ 15 FPS | | | |
| 960H | | 25 FPS | 16CH @ 25 FPS | | | |

