X-ONE THE FUTURE IS ALREADY HERE

Sanremo is revolutionising the concept of grinding, working from one fundamental point: to preserve the characteristics of each coffee, from the bean to the cup.



X-ONE is high precision innovative instrument made to create a new approach to the grinding of coffee, preserving all of its aroma and volatile compounds.

The inspiration comes from the bartenders: to protect the whole coffee bean, to grind just what you need just when you need it.

Without loss of aroma, without product waste, with constancy and repeatability.

3 GRINDERS IN 1

Double hopper of 1.2 kg able to have two different types of coffee, with <u>independent dosages</u>.

Bypass drawer: it's possible to make a <u>grind ad hoc</u> with a third type of coffee.

PRE-PREPARED GRINDING

X-ONE is the only coffee grinder which integrates a system of <u>weighing of</u> coffee beans before grinding releasing the predetermined amount, thus preserving all the aromas of coffee.







0000 000 00



PRODUCT PREVIEW

DESIGN AND PRECISION

The choice is yours! X-ONE is at your command: you can set **grinding speed**, **distance between the grinders, weight of the coffee** from grind.



Electronic and micrometric management of the distance between the grindstones, in order to quickly adapt it to the pre-set in use. The regulation of very high precision and an effective system compensation of mechanical clearances make the granulometry repeatable over time, even through moments

of intense use.

Grinding speed

1000 rpm / 1200 rpm / 1400 rpm independent for each hopper. Possibility of setting a 4th custom speed (range 800÷1500 rpm) from the display.

Inverter high performance

The grinding motor's speed and torque remain constant, even under different installation conditions. Available in the following versions: 100÷127 Vac 50/60 Hz 1550 W 200÷250 Vac 50/60 Hz 1600 W

Dosage

- independent for each hopper
 the precision balance allows
 you weigh from 7 to 30 g
- the automatic <u>pre-dispensing function</u>
 freshly brews a new dose of coffee
 as soon as the previous one has been
 consumed, <u>increasing productivity</u>.



BYPASS

80

The bypass drawer it's a <u>third independent</u> <u>hopper</u>, both for <u>"Single dose"</u> use and as a function <u>"Grocery"</u> (contains up to 250 grams of coffee).



The dedicated screen allows you to set the distance between the grinders and the desired bypass speed.



Filter holder support Accessories supplied as standard: 1 Containment cone 2 Spout for directing the coffee flow

(can be used alternatively) A Height adjustable tab for portafilter


stability, with non-slip covering.

M Manual coffee dispensing buttons to <u>manually supplement</u> <u>the doses</u>.



EMPTY CHAMBER Grinding

After each delivery, the grinding chamber it is <u>always released</u> guaranteeing low retention in the grinding system.



Benefits:

Adjustment of the grinder facilitated after each dispensing, without waste.

No risk of rancidity of the residual product.

Easy coffee change, avoiding product loss.



Vertical flat grinder Ø 98 mm This is the ultimate in performance and durability, engineered for both espresso and filter coffee. The "Black Diamond" DLC treatment facilitates the output of the ground coffee thanks to the low coefficient of friction which, combined with the particular chamber of grinding, reduces the electrostaticity of the coffee.



PRODUCT PREVIEW

00

Ó

SAVE YOUR PRESETS

X-ONE is at your service with **12 presets that can be set with mixed speeds, grain size and weight**, to better manage the different types of coffee and covering every need, from the filter to the espresso.



4.3 " HMI Display in tempered glass Clean crisp graphic interface to keep everything under control. Researched design

for maximum visibility

during the grinding process.

Indication of the <u>temperature outside</u> <u>the grinder</u> on the display in order to more accurately adjust the grinding throughout the day.





Through the **menu** you can constantly monitor the state of health of the machine, regulate and adjust, calibrate the balance (resetting to zero) use the Purge cycle

regulate and adjust, calibrate the balance (resetting to zero), use the Purge cycle and complete cleaning of the machine.



USB port for exporting the dosing pre-sets and grinding parameters stored on your X-ONE to .CSV files or for importing new ones. This way you can create your own personal database and share it with whomever you want.

ণ্ট

The USB port also allows the user to import/export machine configuration parameters and perform firmware updates.



The name of the coffee variety in use can be applied to the hopper using a magnet.



Removable filter holder support for greater convenience during the filling of the takeaway bags and adjustable to adapt to different sizes.

Removable dust plate



Cleaning Native hopp

ONE

Native hopper cleaning functions and automatic grinding motor release if the outlet becomes blocked or clogged. Dosing hopper auger removable without tools to facilitate internal cleaning.



Weighing basket completely removable for easy cleaning.



Ventilation Electronically managed cooling system with built-in diagnostics.



Easy service

Maintenance is not a problem, thanks to the easily removable panels and the dislocation of components.

4 adjustable feet.