

INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN | CHROME OR BLACK FINISH

ST200

THANK YOU FOR CHOOSING STEEL HORSE AUDIO!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.


WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

1 Classic 200W Compact Motorcycle Amplifier



2 1" Handlebar Clamp/Bracket



1 G-Series 4" Pioneer Speakers in Waterproof housings



2 1-1/4" Handlebar Clamp/Bracket



1 Amplifier Wire Harness



6 Cable Ties



1 3.5mm (headphone) to RCA (amplifier) cable



STEELHORSEAUDIO.COM

800-823-5310 | INFO@STEELHORSEAUDIO.COM

Steel Horse Audio #237 | 1540 Main St, Bldg 218 | Windsor, CO 80550



INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN

ST200

-CONTINUED-

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

WHEN CONNECTING POWER AND GROUND WIRES ENSURE THAT THE RED POWER WIRE IS FUSED AT THE POINT WHERE IT IS CONNECTED TO THE VEHICLE'S BATTERY. FAILURE TO DO SO CAN RESULT IN DAMAGE TO THE VEHICLE IF A SHORT CIRCUIT DEVELOPS BETWEEN THE VEHICLE CONNECTION POINT AND THE PRODUCT.

WARNING

THE END USER'S SAFETY DEPENDS UPON PROPER INSTALLATION OF THIS PRODUCT. IF A STEP IN THESE INSTRUCTIONS IS NOT WITHIN YOUR CAPABILITIES OR YOU DO NOT HAVE THE CORRECT TOOLS, HAVE YOUR DEALER PERFORM THE PROCEDURE. IMPROPER INSTALLATION OF THIS PRODUCT COULD RESULT IN DEATH OR SERIOUS INJURY.

ACCIDENTAL VEHICLE START-UP COULD CAUSE DEATH OR SERIOUS INJURY, REMOVE THE MAIN FUSE BEFORE PROCEEDING.

INTRODUCTION

Thank you for purchasing this Steel Horse Audio ST200 Motorcycle Speaker System that is designed to work with any audio devices with a headphone jack including iPhone® and Android® smartphones and tablets. This easy to install and use, all in one unit is capable of transforming your mobile audio device or phone into the center of your motorcycle's audio system. Designed to mount on any motorcycle handle bars with a 1" or 1-1/4" diameter (other sizes available upon request for 7/8", 1-1/8" and 1-1/2"). Congratulations and enjoy the ultimate audio experience!

FEATURES

AMPLIFIER SPECS:

- Compatible with any audio device or phone with a headphone jack, including Android & iPhone
- Easy to install with simple wiring to speakers and power
- Adjustable gain and variable crossover (L/OFF/H)
- Measures just 1.5" x 2.5" x 4" for easy mounting
- Includes power, ground, remote on/off (to prevent battery drain) and output connections 4"

SPEAKER SPECS:

- Steel housings with triple plate chrome or satin black finish
- Measures 4.75" Diameter by 3" depth mounting size for easy mounting, even behind a windshield
- Includes two pair of bar mount brackets: 1" and 1-1/4" (1-1/2" available upon request)
- 200 Watts Peak RMS Power | ~5 amps power draw

INSTALLATION

The Steel Horse Audio ST200 Classic Edition Motorcycle Speaker System can be used with any 12-volt battery and can be mounted to a variety of bars using the included hardware. Mount the speakers where they have sufficient clearance, position the speakers so the speakers are directly at the rider.

STEP 1

MOUNT BRACKETS TO HANDLEBAR FIRST, THEN INSTALL SPEAKERS

Determine the diameter of the handlebar and use either the 1" Bracket or the 1-1/4" Bracket

Note: If you have a different diameter handlebar (7/8", 1-1/8" or 1-1/2"), please request that bracket separately from us.



INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN

ST200

-CONTINUED-

- STEP 2** Install brackets on handlebars where speakers do not obstruct the riders view (such as the handlebars, engine guards or highway/crash bars). Use allen screws that are included on the bracket. The brackets themselves will tighten to the bar when the speakers are installed
- STEP 3** Once brackets are installed, add the speakers:
A) Remove the nut and lock washer only and feed the speaker wire through the bracket hole and attach each speaker to the bracket. Put the lock washer and nut back on through the wire and tighten speaker to bracket. (Flat washer and lock washer go on the bottom). *Do not over-tighten!*
- STEP 4** Adjust the speakers so they are directed at the rider's head. To adjust, just slightly loosen the nut on the speaker stem and move the speaker up or down to align. Make sure all screws are securely fastened and tightened.
- STEP 5** Route speaker wires through the bike's frame to where the amplifier will be installed and proceed to the next steps in amplifier and power connection.




NOTICE

SECURE THE WIRING AWAY FROM MOVING PARTS, PINCH POINTS, OR EXTREME HEAT. STEEL HORSE AUDIO WILL NOT PROVIDE WARRANTY COVERAGE ON ANY ELECTRICAL COMPONENT THAT FAILS DUE TO PINCHED, CRIMPED, BROKEN, ABRADED, MELTED, OR FRAYED WIRES.

AMPLIFIER & POWER CONNECTION

- STEP 1 AMPLIFIER MOUNTING**
Find a place to mount the amplifier away from direct exposure to the elements such as a tool compartment, under the seat, fork bag, saddlebag, swing arm bag, windshield bag, etc. Most places will be fine, but try to avoid areas that could cause extreme overheating (such as tight places wrapped in foam or cotton). The amp can get some moisture but is not waterproof!
Note: Keep the included fuse off the fuse holder until all wiring connections have been made and secured.



- STEP 1 AMPLIFIER POWER CONNECTION**
Connect the Red power wire (w/ fuse) from the wire harness to the positive terminal on the battery. The Black wire is a ground wire and needs to be attached to the negative terminal on the battery. (or to the vehicle's chassis where paint has been removed. The shorter the wire, the better)
- STEP 2** Take the ORANGE remote-on wire and run it to a switched power source (headlight, taillight, etc) or to Bluetooth® Receiver + Controller Add-on (purchased separately). If orange, black & red wires are not connected, system will NOT work.



NOTICE

***When plugging the harness in to the amp, be sure to match up the plug for ORANGE with (R) for "Remote" and RED to (B+) (Battery 12v+). It should lock in place.**



INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN

ST200

-CONTINUED-


Speaker to Amplifier connection

Connect the speaker wires to the corresponding wires on the amplifier as follows:

- STEP 1** Connect the **SQUARED** wire w/ **WHITE LETTERING** from the **RIGHT** speaker to the **GREEN/WHITE** wire from the amp (R-)
- STEP 2** Connect the **ROUNDED** wire from the **RIGHT** speaker to the **SOLID GREEN** wire from the amp (R+)
- STEP 3** Connect the **SQUARED** wire w/ **WHITE LETTERING** from the **LEFT** speaker to the **BLACK/WHITE** wire from the amp (L-)
- STEP 4** Connect the **ROUNDED** wire from the **LEFT** speaker to the **SOLID BLACK** wire from the amp (L+)

Connect the music source or audio device

- STEP 1** You can connect any audio device with a headphone jack using the included RCA to 3.5mm cable. Connect RCA end to amplifier RCA inputs & other end to headphone port of your audio device/mobile. Note: Please note with this type of connection, the audio source will control the volume of the system.



If you added a Bluetooth music source option, please follow these steps:

- STEP 1** *Bluetooth Controller (Satechi)* - Follow instructions included with the controller to pair to your Bluetooth® audio device. Once paired, mount it to your handlebars using the included mount. Plug your audio device into the system using the RCA to 3.5mm cable and this controller will adjust the volume and tracks on your audio device wirelessly. Follow the included instructions for operation.
- STEP 1** *Bluetooth Receiver + Controller (MTX)* - Take the **ORANGE** remote-on wire from the amplifier and run it to where you will install your Bluetooth controller. The system will turn on and off using the controller. (It will also turn Off automatically after 5 minutes, when there is no active Bluetooth device connection, to prevent battery drain). Next, mount the controller to the handlebars using one of the included mounts. Run the red (+) wire to battery positive and black (-) wire to battery negative (or to the vehicle's chassis where paint has been removed, the closer, the better). Connect the blue remote-on wire to the orange wire from the amp (from step 3). Connect the included 3.5mm to the female output on the Bluetooth controller and connect the other end to female input on the amplifier. Follow the included instructions for operation.



INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN

ST200

-CONTINUED-

FINAL STEPS

- STEP 1** When first listening to your system, you will need to adjust the levels and/or EQ on your audio device as well as the amplifier gain level. We recommend starting the gain at about half way and slowly turning it up until you reach optimal sound quality.
- STEP 2** The amplifier variable crossover switch should always be at H (more volume, less bass) or Off (more bass, less volume) setting

NOTICE

Keep the amplifier input cable (headphone jack to RCA) from touching any bare metal when there is no device plugged into the jack, or you may get static or popping through the speakers when the bike is on.



INSTALLATION INSTRUCTIONS

ST200 CLASSIC EDITION WITH AUX-IN

ST200

-CONTINUED-

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses, and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, this is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, you are encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a different circuit than the one to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

5-YEAR WARRANTY

Steel Horse Audio warrants that any Steel Horse Audio products sold hereunder, shall be free of defects in materials & workmanship for a period of five (5) years from the date of purchase by the consumer excepting the following provisions:

1. Steel Horse Audio shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Steel Horse Audio shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Steel Horse Audio product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Steel Horse Audio & a customer.
4. Steel Horse Audio products are often intended for use in specific applications. Steel Horse Audio makes no warranty if used in applications other than intended.
5. Steel Horse Audio speaker systems are warranted for five (5) years from the date of purchase by the consumer.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Steel Horse Audio warranty. If unsure, please contact the place of purchase to verify they are an authorized Steel Horse Audio reseller.

RETURN POLICY

Merchandise may be returned up to 60 days from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 STEEL HORSE AUDIO, LTD. ALL RIGHTS RESERVED

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

STEELHORSEAUDIO.COM

800-823-5310 | INFO@STEELHORSEAUDIO.COM

Steel Horse Audio #237 | 1540 Main St. Bldg 218 | Windsor, CO 80550

