

QUASAR

Version

Wall 60 cm - Black - 800 m³/h

Collection

Design

EAN code

8034122353982



The photograph is purely for information
It may not correspond to the selected version.

FEATURES

- Black tempered glass**
- Perimeter suction**
- Touch control + 24 h function**
- LED lighting**
- Metallic grease filter, removable and washable**
- Charcoal filter included**
- Possible to duct wall mounted from rear**
- Optional Chimney**

OPTIONAL ACCESSORIES

KACL.815

Protective cleaning cloths for stainless steel (box 10 pcs)

KACL.798#41F

Remote under-roof motor 950 m³/h

KACL.770#41F

Remote under-roof 1100 m³/h
Brushless

KACL.786#41F

Outdoor extractor fan 1000 m³/h

KACL.796#4AF

Outdoor extractor fan 1500 m³/h

KACL.797#4AF

Remote under-roof motor 1300 m³/h

TECHNICAL FEATURES

Installation type

Wall

Dimensions

60 cm

Finishing

Black tempered glass finishing
Scotch brite stainless steel

Motor

800 m³/h

Type of control

Touch control

Speed settings

4

Lighting

Led 2x1,2 W - 3200 K

Filter

Metallic filter "Base" - 278x301 mm - 2 pz

Charcoal filter

Round charcoal filter Ø170 mm - Type 6 - included

Minimum distance

Gas hob: 52 cm

Electric hob: 52 cm

PACKAGING: WEIGHTS AND VOLUMES

Gross weight

31 kg

Net weight

26 kg

Volume

0,30 m³

Packaging size

Length

775 mm

Height

705 mm

Depth

550 mm

CONSUMPTION AND CONNECTION FEATURES

Maximum consumption

280 W

Current

220-240V

Frequency

50-60Hz

Plug type

Shuko

MOTOR TECHNICAL SHEET

Maximum capacity

750 m³/h

I.E.C. 61591

Maximum noise

66 dB(A)re1pW

I.E.C.60704-2-13

Maximum pressure (Pa)



510 Pa

Maximum power motor

224 W

ENERGY CLASS

A



QUASAR

Version

Wall 60 cm - Black - 800 m³/h

Collection

Design


EAN code

8034122353982

MOTOR TECHNICAL SHEET

Speed motor	1	2	3	4
Noise dB(A)re1pW-I.E.C.60704-2-13	46	53	58	66
Capacity (m ³ /h) I.E.C.61591 Tubazioni normalizzate	295	390	500	750
Maximum pressure (Pa)	390	440	490	510
Power motor (W)	130	150	178	224
Air outlet	150	150	150	150

CAPACITY / PRESSURE



QUASAR

Version

Wall 60 cm - Black - 800 m³/h


Collection

Design

EAN code

8034122353982

ENERGY LABEL



PF		
S	Falmec Spa	
M	Wall 60 cm - Black - 800 m ³ /h	
AEC	55,9	kWh/a
ECC	A	
FDE	29,4	
FDEC	A	
LE	38,3	
LEC	A	
GFE	76,0	
GFEC	C	
Qmin	295,0	m ³ /h
Qmax	500,0	m ³ /h
Qboost	750,0	m ³ /h
SPEmin	46	dBa
SPEmax	58	dBa
SPEboost	66	dBa
PO	-	W
PS	0,48	W
PI		
F	0,9	
EEl	52,2	
Qbep	430,0	m ³ /h
Pbep	404	Pa
Qboost	750,0	m ³ /h
Wbep	164,0	W
WL	2,80	W
Emiddle	108	lux
Lwa-SPEmax	58	dBa

PF_Product fiche according to 65/2014 S_Supplier name / M_Model identification / AEC_Annual Energy Consumption (AEC hood) / EEC_Energy Efficiency class / FDE_Fluid Dynamic Efficiency (FDE hood) / FDEC_Fluid Dynamic Efficiency class / LE_Lighting Efficiency (LE hood) / LEC_Lighting Efficiency class / GFE_Grease Filtering Efficiency / GFEC_Grease Filtering Efficiency class / Qmin_Air flow (in m³/h) at min speed in normal use / Qmax_Air flow (in m³/h) at max speed in normal use / Qboost_Air flow (in m³/h) at intensive or boost setting (max air-flow) / SPEmin_Airborne acoustical A-weighted sound power emissions at min speed in normal use / SPEmax_Airborne acoustical A-weighted sound power emissions at max speed in normal use / SPEboost_Airborne acoustical A-weighted sound power emissions (in dB) at intensive or boost setting / PO_Power consumption in off mode (Po) / Ps_Power consumption in stand by mode (Ps). **PI_Additional information according to 66/2014** F_Time increase factor / EEl_Energy Efficiency Index / Qbep_Measured air flow rate at best efficiency point / Pbep_Measured air pressure at best efficiency point / Qboost_Maximum air flow / Wbep_Measured electric power input at best efficiency point / WL_Nominal power of the lighting system / Emiddle_Average illumination of the lighting system on the cooking surface / Lwa=SPEmax_Sound pressure level at the highest speed.