

LED MULTI / TRI COLOUR PANEL LIGHTS



PRODUCT FEATURES

- Input voltage: 220~240V AC 50/60Hz
- Material: aluminium, PMMA & PS
- White trim/frame
- Wattage: 36W & 60W
- Power factor: 0.95
- Epistar SMD2835 LED chips
- CCT changeable: 3000K - 4000K - 6500K
- Flex & plug with male joiner included (L: 1200mm)
- External driver with female joiner
- Driver dimensions: (L140 x W 40.5 x D 30mm)
- Distance lead to driver: 1220mm & Driver to panel: 85mm
- Ambient temp: -20 to +40°C
- Not suitable for dimming
- Suitable for 2-way switching
- Suitable for use with PIR & microwave sensors
- **IPART & VEET approved (January 2018)**

PANELM01 (595x595mm)



PANELM02 (295x1195mm)



PANELM03 (595x1195mm)

LIFE TIME 35,000 HOURS	BEAM 110°	IP20 RATED	WARRANTY 3YEARS REPLACEMENT
------------------------------	--------------	---------------	-----------------------------------

PART NO.	DESCRIPTION	KELVIN (K)	LUMENS (LM)	WATT (W)	CRI	DIMENSION (mm)	WEIGHT (KG)	BOX (CM)	CARTON QTY
PANELM01	PANEL LED TBAR WH Multi / Tri colour 595mm X 595mm 36W	3000/4000/6500	2900/3100/3000	36	80	595x595x9.2	3.6	67.5x63x5.5	4
PANELM02	PPANEL LED TBAR WH Multi / Tri colour 295mm X 1195mm 36W	3000/4000/6500	2900/3100/3000	36	80	295x1195x9.2	3.7	127.5x33x5.5	4
PANELM03	PANEL LED TBAR WH Multi / Tri colour 595mm X 1195mm 60W	3000/4000/6500	4800/5100/5000	60	80	595x1195x9.2	7.3	129.5x65x5.2	1

UPDATED ON 20.02.2018

Tel: (02) 9938 7100 | Fax: (02) 9938 7115 | Email: sales@clalighting.com.au

Website: www.clalighting.com.au

Follow us: facebook.com/CLALighting