

D O V I V I O V[™] **d**108

The Dominion[™] powered subwoofers benefit from JL Audio's expertise in driver and amplifier design to arrive at a unique solution for applications requiring a compact, more affordable subwoofer.

Unlike any other product in its price class, the Dominion[™] powered subwoofer employs a purposeengineered, long excursion driver, built on JL Audio's exclusive DMA motor optimization technology. This leads to reduced distortion at higher output levels, as well as improved dynamic tracking and resolution.

The Dominion[™] amplifier is also purpose-engineered, featuring an advanced Class D design, with a tightlyregulated switching power supply (another rarity in this price class). These technologies ensure that the Dominion[™] powered subwoofer remains in its comfort zone, well past the point where most small subwoofers run out of power or driver capability.

Dominion[™] powered subwoofers can be used in full home theater systems, media room systems, dedicated two-channel music systems, desktop audio workstations and small recording studios, just to name a few potential applications. High-level inputs even make it possible to add a subwoofer to systems lacking line outputs. The available Wireless Link port operates with a JLINK[™] TRX system (sold separately) to deliver an invisible, cable-free connection from your source unit, up to 100 feet (30 meters) away.

Every Dominion[™] powered subwoofer is precision-built in JL Audio's U.S. factory to deliver years of listening enjoyment.

Dominion[™] d108 Features:

Unbalanced Inputs: Stereo or Mono (two RCA jacks)

High-Level Inputs: Stereo or Mono (removable plug)

Wireless Inputs: Bit-Perfect PCM Stereo Digital via 2.4 GHz Wireless (when used with JLINK™ TRX - sold separately)

Input Grounding: Selectable (Isolated or Grounded)

Level Control: Variable: full mute to +15 dB over reference gain

Power On/Off: Automatic Signal-Sensing only

Low-Pass Filter: 24 dB per octave with Linkwitz-Riley alignment

Low-Pass Cutoff Frequency Range: Variable: 25 Hz – 130 Hz

Polarity: 0 or 180 degrees

Phase: Variable from 0 – 280 degrees, referenced to 80 Hz



FRONT

Dominion[™] d108 Specifications:

Enclosure Type: Sealed

Drivers: Single 8-inch (nominal diameter)

Frequency Response: (anechoic) 31 – 112 Hz (±1.5dB) –3 dB at 29 Hz / 119 Hz –10 dB at 21 Hz / 143 Hz

Input Impedance: Line Inputs: 20 kΩ High-Level Inputs: 4.4 kΩ

Effective Piston Area: 32.18 sq. in. (0.0208 sq. m)

Effective Displacement: 80 cu. in. (1.3 liters)


Amplifier Power: 500 watts RMS short-term


Dimensions* (H x W x D): 11.37 in. x 10 in. x 13.23 in. 289 mm x 254 mm x 336 mm

Net Weight: 26.4 lbs. (12 kg)


Cabinet Finish: High-Gloss Black or Black Ash Vinyl Veneer

Built in USA with imported and domestic components





SIDE WITH GRILLE



* All height dimensions include feet, depth dimensions include grilles.

"JL Audio", "Ahead of the Curve" and the JL Audio logo are registered trademarks of JL Audio, Inc. ©2015 JL Audio, Inc. • U.S. PATENTS: #5,734,734 #6,501,844 Other U.S. & Foreign patents pending. Due to our policy of continuous product development, all specifications are subject to change without notice.

www.jlaudio.com

10369 North Commerce Parkway • Miramar, Florida • 33025 • USA

GEDIA Association Member

SKU#97270 05-2015 Printed in U.S.A.