OVENS



VC66E SERIES DOUBLE DECK, DEEP DEPTH **ELECTRIC CONVECTION OVENS**



Model VC66ED Shown with optional casters









SPECIFICATIONS

Double section, deep depth electric convection oven, Vulcan Model No. (VC66ED) (VC66EC). Stainless steel front, sides, top and legs. Independently operated stainless steel doors with double pane windows. Non-sag insulation applied to the top, rear, sides, bottom and doors. Porcelain enamel on steel oven interiors measure 29"w x $26\frac{1}{8}$ "d x 20"h. Two interior oven lights per section. Five nickel plated oven racks per section measure 281/4" x 241/2". Eleven position nickel plated rack guides with positive rack stops per section. Each section heated by electric solid sheath elements rated at 12 KW. Furnished with a two speed ½ H.P. oven blower-motor per section. Oven cool switch for rapid cool down. 208 or 240 volt, 60 Hz, 1 or 3 phase.

Exterior Dimensions:

 $40\frac{1}{4}$ "w x $45\frac{1}{8}$ "d (includes motor & door handles) $41\frac{3}{4}$ "d (includes motor only) x 70"h on 8" legs.

NSF listed. UL listed. UL listed to Canadian safety standards.

□ VC66ED Solid state temperature controls adjust from

150° to 500°F. 60 minute timer with audible

alarm.

□ VC66EC Computer controls with digital time and

temperature readouts. 99-hour timer with audible alarm. Roast and Hold cycle.

One hundred programmable menu selections.

Shelf I.D. programming.

STANDARD FEATURES

- Stainless steel front, sides, top and legs.
- Independently operated stainless steel doors with double pane windows.
- 25 total KW.
- $\frac{1}{2}$ H.P. two speed oven blower-motor.
- Moisture vent damper control.
- Oven cool switch for rapid cool down per section.
- Porcelain enamel on steel oven interiors.
- Five nickel plated oven racks with eleven rack positions per section.
- One year limited parts and labor warranty.

OPTIONS

- Complete prison package.
- ☐ Security screws only.
- □ Casters.
- ☐ Simultaneous chain driven doors.
- ☐ 480V/60 Hz/1 or 3 phase.
- ☐ Second year extended limited parts and labor warranty.

ACCESSORIES

- ☐ Stainless steel rear motor enclosure.
- □ Extra oven rack(s).
- ☐ Rack hanger(s).
- ☐ Stainless steel drip pan.
- ☐ Down draft flue diverter for direct vent connection.






VC66E SERIES DOUBLE DECK, DEEP DEPTH ELECTRIC CONVECTION OVENS


OPTIONAL VOLTAGES


- ☐ 480 volt, 60 Hz, 3 phase.
- ☐ 220/380 volt, 50 Hz, 1 phase, 3 wire.
- ☐ 220/380 volt, 50 Hz, 3 phase, 4 wire.
- ☐ 240/415 volt, 50 Hz, 3 phase, 4 wire.

CLEARANCES

	Compustible	Non-Combus
Rear	2"	2"
Right Side	4"	4"
Left Side	1"	1"







		3	PHAS	SE	NOMINAL AMPS PER LINE WIRE											WEIGHT			
			LOAD		3 PHASE										WITH		WITHOUT		
MODEL	TOTAL CONN.	KW PER PHASE			208 VOLT			240 VOLT			480 VOLT			1 PHASE		SKIDS & PACKAGING		SKIDS & PACKAGING	
NO.	KW	X-Y	Y-Z	X-Z	Х	Υ	Z	Х	Υ	Z	Х	Υ	Z	208V	240V	LBS.	KG	LBS.	KG
VC66E	25	8	8	9	70	66	70	66	58	66	28	30	30	120	104	926	420	810	368



a division of ITW Food Equipment Group LLC

P.O. Box 696 Louisville, KY 40201 Toll-free: 1-800-814-2028 Local: 502-778-2791 Quote & Order Fax: 1-800-444-0602

