Single Ice Machine Configurations

Ice-O-Matic offers a full line of bins for most applications. From low profile slope-front bins to high capacity space-saving uprights, we have a bin to meet any need. The following table will help you create the system you need in a safe and cost effective manner.

		Application Bin Storage Ibs (kgs)	Approximate Shipping Weight Ibs (kgs)	CIM Series Cube Ice Makers		ICE Series Cube Ice Makers			Pearl Ice® Ice Makers	Flake Ice Machine
Bin Model No.				<b>22"</b> (565 mm) wide	<b>30"</b> (762 mm) wide	<b>22"</b> (559 mm) wide	<b>30"</b> (762 mm) wide	<b>48"</b> (1,219 mm) wide	<b>21"</b> (533 mm) wide	<b>21"</b> (533 mm) wide
B25PP*	Slope Front	242 (110)	74 (34)	KBT19	$\triangle \triangle$	KBT19	ΔΔ	N/A	KBT19	KBT19
B4OPS	Slope Front	344 (156)	103 (47)	KBT19	$\triangle \triangle$	KBT19	$\triangle \triangle$	N/A	KBT19	KBT19
B42PS	Slope Front	351 (160)	99 (45)	N/A	N/A	ΔΔ	N/A	N/A	KBT24	KBT24
B55PS	Slope Front	510 (232)	125 (57)	KBT19	$\triangle \triangle$	KBT19	$\triangle \triangle$	N/A	KBT19	KBT19
B11OPS	Slope Front	854 (388)	163 (74)	N/A	BPF-1***	N/A	BPF-1***	$\triangle \triangle$	KBT23	KBT23
B700-30	Upright	680 (308)	212 ( 96)	$\triangle \triangle$	$\triangle \triangle$	$\triangle \triangle$	$\triangle \triangle$	N/A	$\triangle \triangle$	ΔΔ
B1000-48	Upright	1000 (454)	268 (122)	ΔΔ	$\triangle \triangle$	ΔΔ	ΔΔ	$\triangle \triangle$	ΔΔ	ΔΔ
B1300-48	Upright	1320 (599)	270 (123)	ΔΔ	$\triangle \triangle$	ΔΔ	ΔΔ	ΔΔ	ΔΔ	ΔΔ
B1325-60	Upright	1325 (601)	320 (146)	ΔΔ	$\triangle \triangle$	ΔΔ	$\triangle \triangle$	$\triangle \triangle$	$\triangle \triangle$	ΔΔ
B1600-60	Upright	1660 (753)	340 (154)	ΔΔ	ΔΔ	ΔΔ	ΔΔ	ΔΔ	ΔΔ	$\triangle \triangle$

△△ Kit not required.
△△\*\* Ice clumping issues may arise.

\* Rotocast finish

N/A Not Applicable

Side-by-Side Ice Machine Configurations

There are times when it is desirable to install (2) ice machines side by side on a bin. The reasons may range from gaining maximum output to creating redundancy. Ice-O-Matic offers an array of kits and bins with custom order tops for just such applications. The following table will help you create the system you need in a safe and cost effective manner.

		Application Bin Storage Ibs (kgs)	Approximate Shipping Weight lbs (kgs)	CIM Series Cube Ice Makers		ICE Series Cube Ice Makers			Pearl Ice® Ice Makers	Flake Ice Machine
Bin Model No.	Style			<b>22"</b> (565 mm) wide	<b>30"</b> (762 mm) wide	<b>Two 22"</b> (559 mm) wide	<b>Two 30"</b> (762 mm) wide	<b>Two 48"</b> (1,219 mm) wide	<b>Two 21"</b> (533 mm) wide	<b>Two 21"</b> (533 mm) wide
B25PP*	Slope Front	242 (110)	74 (34)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
B4OPS	Slope Front	344 (156)	103 (47)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
B42PS	Slope Front	351 (160)	99 (45)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
B55PS	Slope Front	510 (232)	125 (57)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
B11OPS	Slope Front	854 (388)	163 (74)	N/A	N/A	N/A	N/A	N/A	KBT22	KBT22
B700-30	Upright	680 (308)	212 ( 96)	N/A	N/A	N/A	N/A	N/A	N/A	N/A
B1000-48	Upright	1000 (454)	268 (122)	ΔΔ	N/A	ΔΔ	ΔΔ	N/A	ΔΔ	ΔΔ
B1300-48	Upright	1320 (599)	270 (123)	ΔΔ	N/A	ΔΔ	ΔΔ	N/A	ΔΔ	$\triangle \triangle$
B1325-60	Upright	1325 (601)	320 (146)	ΔΔ	N/A	ΔΔ	N/A	N/A	ΔΔ	ΔΔ
B1600-60	Upright	1660 (753)	340 (154)	ΔΔ	N/A	ΔΔ	N/A	N/A	ΔΔ	ΔΔ

 $\Delta\Delta$  Kit not required.

O\* Must use remote or water cooled model only; ice clumping issues may arise.

\* Rotocast finish

N/A Not Applicable



<sup>\*\*</sup> ICE1506 is compatible with B700-30, B1000-48, B1300-48, B1325-60 & B1600-60.

<sup>\*\*\*</sup> BPF-1 used with B110 ONLY. If you have an older model B100 bin use the KBT5.