

COMMERCIAL

Digital Cabinets Reach-In Freezer, 72 cu.ft -Stainless Steel (R290)



Digital control with cabinet temperature display. Self-closing and onsite reversible door feature lock and key.

R290 gas in the refrigeration circuit. ETL Safety and Sanitation certifications. 3/5 Years warranty.

	Č
ITEM #	
MODEL #	
NAME #	
<u>SIS #</u>	
AIA #	

Main Features

- External temperature display.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worryfree performance.
- Electronic Digital Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.
- Bottom mounted cooling unit slides out for easy access and cleaning.

Construction

- Lockable door.
- Reversible door.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

APPROVAL:

Kelvinator Commercial www.kelvinatorcommercial.com USA • 10200 David Taylor Drive • Charlotte, NC 28262 • 1-866-738-1640



Digital Cabinets Reach-In Freezer, 72 cu.ft -Stainless Steel (R290)

Electric

81''-2	2057mm	Front	Electric
			Supply voltage: 738246 (KCHR
·		-##	Electrical power, Plug type:
			Key Inform
			Capacity (Cu.Ft.) Door hinges: External dimensi External dimensi External dimensi Number and type (included): Compressor Hors Type of external Type of internal
			Warranty:
V	1	v	Refrigerat Refrigerant type:
57.5"-1 32.7"-830mm	460mm	Side	Operating tempe Operating tempe Condenser type: Defrost type:
	57.5"-1 32.7"-830mm	Electrical connection Refrigerant Inlet	BI"-2057mm

"||)

15A 125V NEMA 5-15P

5x.

Intertek

Intertek

8246 (KCHRI81R3DF) rical power, max: type:	115 V/1 ph/60 Hz 1 kW USA NEMA 5-20P
y Information:	
city (Cu.Ft.) hinges:	72.0
nal dimensions, Width:	81 " (2057 mm)
nal dimensions, Depth:	32 11/16" (830 mm)
nal dimensions, Height:	82 1/4" (2090 mm)
per and type of doors:	3 Full
per and type of grids Ided):	9 - Coated Steel
oressor Horsepower:	1 1/4
of external material:	430 AISI
of internal material:	304 AISI

3 / 5 years

efrigeration Data

Refrigerant type:	R290
Operating temperature min.:	-8 °F
Operating temperature max.:	-0 °F
Condenser type:	Fin & tube
Defrost type:	Auto Defrost

Digital Cabinets Reach-In Freezer, 72 cu.ft - Stainless Steel (R290)

