# 6455-C

# FROZEN BEVERAGE FREEZER

Two flavor, Countertop, Gravity feed



CE

## Most Compact & Versatile

Two flavor countertop model for frozen beverage and smoothies

## Fast Freeze Down

Patented high efficiency heat exchanger allows fast freeze down with low energy consumption

## Simple Control, Easy Operation

Simple and intuitive control system makes operation and viscosity adjustment easy, swift and more precise

## Low Mix Indicator

Light turns "ON" at low mix to alert operator to add mix

## See-through Dispensing Door

Clear dispensing door design makes product more attractive and serves as great marketing tool

## Standby & Indicator

Maintains product temperature in both mix hopper and freezing cylinder below 4.4°C (40°F) overnight; Indicator light turns ON blue under Standby mode

Perfect solution for alcoholic and non-alcoholic frozen beverages in bars, restaurants, hospitals, schools and kiosks

Intertek

## **Hopper Agitators**

Maintain product consistency and prevent product separation

## Self-closing Dispensing Valves

Automatically prevents product overflow after dispense

## **Safety Protections**

- High pressure switch to prevent compressor overheating
- Thermal overload to protect from motor overheating

## Light Box (Optional)

- Illuminates flavor cards to attract more business
- Changes color to indicate Low Mix and Standby


## **One-hand Operated Spinner (Optional)**

- Adds ability to blend and offer more variaties of treats
- Allows for multi-tasking one-hand operation that helps increase productivity and reduce serving time



# 6455-C

## FROZEN BEVERAGE FREEZER



SPECIFICATIONS	
Flavors	

2 x 3.8L / 4.0qt
2 x 8.0L / 8.5qt
112 serves/hr
152mm/6" on back


2

Weight	Kg/lb	
Net	146 / 325	
Shipping	166 / 369	
Volume	0.48 CBM / 17.10 CBF	

Dimensions	Net (mm/in)	Shipping (mm/in)
Width	476 / 18.7	520/20.5
Depth	651/25.6	853/33.6
Height	950 / 37.4	1090 / 42.9

Electrical	MFS	MCA	Power(kW)
220-240/50/1	15	13	2.0
220-240/60/1	15	13	2.1
110-115/60/1	20	16	1.6

 $\boldsymbol{\cdot}$  Above specifications are subject to change without notice



FEATURES	
Control Systems	Two, Mechanical
Refrigerated Hoppers	
Hopper Agitators	
Standby Mode	
Auto Closing Dispensing Valves	
Low Mix Indicator Light	
Low Mix Indicator Alarm	
Standby Mode	
Standby Indicator Light	
High Pressure Protection	
Thermal Overload Protection	

AVAILABLE OPTIONS	
Top Air Discharge Chute	$\checkmark$
Spinner	
Light Box	$\checkmark$