

HEATER PROOFERS NON-INSULATED STANDARD FULL & 1/2 HEIGHT 100% PRE-TESTED ELECTRICAL ASSEMBLY

- Heavy Duty, aluminum construction designed for durability.
- Easy to Clean.
- Forced air design provide even heat distribution.
- 5" polyurethane plate casters for easy maneuverability and stability. Front casters are provided with brakes.
- Easy dual proof/heat control: Available in Digital and Analog designs.
- "Proof/humidity" mode: Up to 95% humidity at 110°F (43°C)
- "Heat" mode: Maximum Temperatures up to 180°F (82°C)
- Corner bumpers provide protection to unit, associates & fixtures.
- Clear door, extruded, anodized aluminum frame will not dull. A tight fit gasket is installed on the inside door frame. Half height has a poly top.
- Door opens 270 degrees. Door lifts off for easy cleaning and accessibility.
- Control drawer is removable for quick and easy cleaning and maintenance.
- Drip trough catches condensation. Internal water pan collects condensation or is used in proofer mode.
- All controls are accessible without opening cabinet door. Easy to read real time LED thermometer display.
- Pan Capacity: 35 - 18" x 26" pans NHPL-1836C
10 - 18" x 26" pans NHPL-1810HHC

Electrical specifications:

- 120 Volt-60 Hz, NEMA 5-15P
- 1440 Watts: 14.0 AMPS - Plug into any standard 110 outlet.



NHPL-1836C-DGT

| Model Number | Order# | Overall Dimensions | | | Approx. Ship Wt |
|----------------|---------|--------------------|--------|--------|-----------------|
| | | Width | Length | Height | |
| | | (in) | (in) | (in) | (lb) |
| NHPL-1836C-DGT | 1078985 | 21 | 30¾ | 66½ | 136 |
| NHPL-1836C | 684684 | 21 | 30¾ | 66½ | 136 |
| NHPL-1810HHC | 684625 | 21 | 30¾ | 30½ | 91 |

Caster Information

Swivel Plate Caster with 5" Polyurethane Wheel 738A (128784)
Swivel Plate Caster with 5" Polyurethane Wheel & Brake 738ABK (204185)
5" Polyurethane Wheel 7112 (122180)

Freight Class: 175



NHPL-1810HHC
Fits under counters
and tables.