



## Safety Data Sheet

Copyright, 2017, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilising 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

<b>Document group:</b>	27-4388-8	<b>Version number:</b>	13.00
<b>Revision date:</b>	16/03/2017	<b>Supersedes date:</b>	09/03/2017
<b>Transportation version number:</b>	1.00 (27/03/2010)		

This Safety Data Sheet has been prepared in accordance with the REACH Regulation (EC) 1907/2006 and its modifications.

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

3M Perfect-It III 50383 Ultrafina SE

#### Product Identification Numbers

GC-8010-3469-2	GC-8010-3470-0	UU-0016-6332-5	UU-0016-6334-1
7000084649	7000034426	7100062883	7100057579

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### Identified uses

Automotive.

#### 1.3. Details of the supplier of the safety data sheet

**Address:** 3M United Kingdom PLC, 3M Centre, Cain Road, Bracknell, Berkshire, RG12 8HT.  
**Telephone:** +44 (0)1344 858 000  
**E Mail:** tox.uk@mmm.com  
**Website:** www.3M.com/uk

#### 1.4. Emergency telephone number

+44 (0)1344 858 000

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

CLP REGULATION (EC) No 1272/2008

##### CLASSIFICATION:

Specific Target Organ Toxicity-Single Exposure, Category 3 - STOT SE 3; H336

For full text of H phrases, see Section 16.

#### 2.2. Label elements

CLP REGULATION (EC) No 1272/2008

**SIGNAL WORD**

WARNING.

**Symbols:**

GHS07 (Exclamation mark) |

**Pictograms****Ingredients:**

Ingredient	CAS Nbr	% by Wt
Distillates (petroleum), hydrotreated light	64742-47-8	10 - 30
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	1 - 5

**HAZARD STATEMENTS:**

H336 May cause drowsiness or dizziness.

**PRECAUTIONARY STATEMENTS****General:**

P102 Keep out of reach of children.  
 P101 If medical advice is needed, have product container or label at hand.

**Prevention:**

P261A Avoid breathing vapours.  
 P261B Avoid breathing dust.  
 P271 Use only outdoors or in a well-ventilated area.

**Disposal:**

P501 Dispose of contents/container in accordance with applicable local/regional/national/international regulations.

**SUPPLEMENTAL INFORMATION****Supplemental Hazard Statements:**

EUH066 Repeated exposure may cause skin dryness or cracking.  
 EUH208 Contains 1,2-Benzisothiazol-3(2H)-one. May produce an allergic reaction.

**Notes on labelling**

H304 is not required on the label due to the product's viscosity  
 Nota L applied to CAS# 64741-88-4.

**2.3. Other hazards**

None known.

**SECTION 3: Composition/information on ingredients**

Ingredient	CAS Nbr	EC No.	REACH Registration No.	% by Wt	Classification
Non Hazardous Materials	Mixture	231-791-2		40 - 70	Substance not classified as

**3M Perfect-It III 50383 Ultrafina SE**

					hazardous
Dodecamethylcyclohexasiloxane	540-97-6	208-762-8		10 - 30	Aquatic Chronic 4, H413
Distillates (petroleum), hydrotreated light	64742-47-8	265-149-8		10 - 30	Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Flam. Liq. 3, H226; STOT SE 3 H336; EUH066
Aluminium Oxide (non-fibrous)	1344-28-1	215-691-6		1 - 10	Substance with a Community level exposure limit in the workplace
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	265-090-8		1 - 5	Nota L Asp. Tox. 1, H304; EUH066
Glycerin	56-81-5	200-289-5		<= 1	Substance with a Community level exposure limit in the workplace
Decamethylcyclopentasiloxane	541-02-6	208-764-9		0.1 - 1	Aquatic Chronic 4, H413
1,2-Benzisothiazol-3(2H)-one	2634-33-5	220-120-9		< 0.05	Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Dam. 1, H318; Skin Sens. 1, H317; Aquatic Acute 1, H400,M=1

Please see section 16 for the full text of any H statements referred to in this section

For information on ingredient occupational exposure limits or PBT or vPvB status, see sections 8 and 12 of this SDS

**SECTION 4: First aid measures****4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

**Skin contact**

Wash with soap and water. If signs/symptoms develop, get medical attention.

**Eye contact**

Flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. If signs/symptoms persist, get medical attention.

**If swallowed**

Rinse mouth. If you feel unwell, get medical attention.

**4.2. Most important symptoms and effects, both acute and delayed**

See Section 11.1 Information on toxicological effects

**4.3. Indication of any immediate medical attention and special treatment required**

Not applicable

**SECTION 5: Fire-fighting measures****5.1. Extinguishing media**

In case of fire: Use a carbon dioxide or dry chemical extinguisher to extinguish.

**5.2. Special hazards arising from the substance or mixture**

None inherent in this product.

**Hazardous Decomposition or By-Products****Substance**

Carbon monoxide.  
Carbon dioxide.

**Condition**

During combustion.  
During combustion.

**5.3. Advice for fire-fighters**

No special protective actions for fire-fighters are anticipated.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapours, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

**6.2. Environmental precautions**

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

**6.3. Methods and material for containment and cleaning up**

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with detergent and water. Seal the container. Dispose of collected material as soon as possible.

**6.4. Reference to other sections**

Refer to Section 8 and Section 13 for more information

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

Keep out of reach of children. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Avoid release to the environment. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.)

**7.2. Conditions for safe storage including any incompatibilities**

Store away from heat. Store away from acids. Store away from oxidising agents.

**7.3. Specific end use(s)**

See information in Section 7.1 and 7.2 for handling and storage recommendations. See Section 8 for exposure controls and personal protection recommendations.

**SECTION 8: Exposure controls/personal protection****8.1 Control parameters****Occupational exposure limits**

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

<b>Ingredient</b>	<b>CAS Nbr</b>	<b>Agency</b>	<b>Limit type</b>	<b>Additional comments</b>
Aluminium Oxide (non-fibrous)	1344-28-1	UK HSC	TWA(as inhalable dust):10 mg/m <sup>3</sup> ;TWA(as respirable	

Glycerin 56-81-5 UK HSC dust):4 mg/m<sup>3</sup>  
 TWA(as mist):10 mg/m<sup>3</sup>  
 UK HSC : UK Health and Safety Commission  
 TWA: Time-Weighted-Average  
 STEL: Short Term Exposure Limit  
 CEIL: Ceiling

**Biological limit values**

No biological limit values exist for any of the components listed in Section 3 of this safety data sheet.

**8.2. Exposure controls**

**8.2.1. Engineering controls**

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment. Provide appropriate local exhaust ventilation for cutting, grinding, sanding or machining.

**8.2.2. Personal protective equipment (PPE)**

**Eye/face protection**

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Indirect vented goggles.

**Skin/hand protection**

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.

Gloves made from the following material(s) are recommended:

Material	Thickness (mm)	Breakthrough Time
Polymer laminate	No data available	No data available

**Respiratory protection**

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapours and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

**SECTION 9: Physical and chemical properties**

**9.1. Information on basic physical and chemical properties**

<b>Physical state</b>	Liquid.
<b>Specific Physical Form:</b>	Thixotropic liquid.
<b>Appearance/Odour</b>	Solvent odour; pale blue liquid
<b>Odour threshold</b>	<i>No data available.</i>
<b>pH</b>	7.5 - 8.5
<b>Boiling point/boiling range</b>	<i>No data available.</i>
<b>Melting point</b>	<i>Not applicable.</i>
<b>Flammability (solid, gas)</b>	Not applicable.

<b>Explosive properties</b>	Not classified
<b>Oxidising properties</b>	Not classified
<b>Flash point</b>	>= 110 °C [Test Method:Closed Cup]
<b>Autoignition temperature</b>	<i>Not applicable.</i>
<b>Flammable Limits(LEL)</b>	<i>No data available.</i>
<b>Flammable Limits(UEL)</b>	<i>No data available.</i>
<b>Vapour pressure</b>	<i>No data available.</i>
<b>Relative density</b>	0.911 - 1.007 [Ref Std:WATER=1]
<b>Water solubility</b>	Appreciable
<b>Solubility- non-water</b>	<i>No data available.</i>
<b>Partition coefficient: n-octanol/water</b>	<i>No data available.</i>
<b>Evaporation rate</b>	<i>No data available.</i>
<b>Vapour density</b>	<i>No data available.</i>
<b>Decomposition temperature</b>	<i>No data available.</i>
<b>Viscosity</b>	10,000 - 13,000 mPa-s
<b>Density</b>	0.9 - 1 kg/l

**9.2. Other information**

Percent volatile	57.2 %
------------------	--------

**SECTION 10: Stability and reactivity****10.1 Reactivity**

This material is considered to be non reactive under normal use conditions

**10.2 Chemical stability**

Stable.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation will not occur.

**10.4 Conditions to avoid**

Heat.

High shear and high temperature conditions

Sparks and/or flames.

Temperatures above the boiling point.

**10.5 Incompatible materials**

Alkali and alkaline earth metals.

Strong acids.

Strong oxidising agents.

**10.6 Hazardous decomposition products****Substance**

None known.

**Condition**

Refer to section 5.2 for hazardous decomposition products during combustion.

**SECTION 11: Toxicological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 11 are based on UN GHS calculation rules and classifications derived from

**3M assessments.****11.1 Information on Toxicological effects****Signs and Symptoms of Exposure**

Based on test data and/or information on the components, this material may produce the following health effects:

**Inhalation**

Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. Dust from cutting, grinding, sanding or machining may cause irritation of the respiratory system: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, nose and throat pain.

**Skin contact**

Mild Skin Irritation: Signs/symptoms may include localised redness, swelling, itching, and dryness.

**Eye contact**

Dust created by cutting, grinding, sanding, or machining may cause eye irritation: Signs/symptoms may include redness, swelling, pain, tearing, and blurred or hazy vision.

**Ingestion**

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea.

**Toxicological Data**

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

**Acute Toxicity**

Name	Route	Species	Value
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Distillates (petroleum), hydrotreated light	Dermal	Rabbit	LD50 > 3,160 mg/kg
Dodecamethylcyclohexasiloxane	Dermal	Rat	LD50 > 2,000 mg/kg
Dodecamethylcyclohexasiloxane	Ingestion	Rat	LD50 > 50,000 mg/kg
Distillates (petroleum), hydrotreated light	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 3 mg/l
Distillates (petroleum), hydrotreated light	Ingestion	Rat	LD50 > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Dermal		LD50 estimated to be > 5,000 mg/kg
Aluminium Oxide (non-fibrous)	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 2.3 mg/l
Aluminium Oxide (non-fibrous)	Ingestion	Rat	LD50 > 5,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Rabbit	LD50 > 2,000 mg/kg
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	Rat	LD50 > 5,000
Glycerin	Dermal	Rabbit	LD50 estimated to be > 5,000 mg/kg
Glycerin	Ingestion	Rat	LD50 > 5,000 mg/kg
Decamethylcyclopentasiloxane	Dermal	Rabbit	LD50 > 15,000 mg/kg
Decamethylcyclopentasiloxane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 8.7 mg/l
Decamethylcyclopentasiloxane	Ingestion	Rat	LD50 > 24,134 mg/kg

ATE = acute toxicity estimate

**Skin Corrosion/Irritation**

Name	Species	Value
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation

**3M Perfect-It III 50383 Ultrafina SE**

Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Minimal irritation
Glycerin	Rabbit	No significant irritation
Decamethylcyclopentasiloxane	Rabbit	No significant irritation

**Serious Eye Damage/Irritation**

Name	Species	Value
Dodecamethylcyclohexasiloxane	Rabbit	No significant irritation
Distillates (petroleum), hydrotreated light	Rabbit	Mild irritant
Aluminium Oxide (non-fibrous)	Rabbit	No significant irritation
Distillates (petroleum), solvent-refined heavy paraffinic	Rabbit	Mild irritant
Glycerin	Rabbit	No significant irritation
Decamethylcyclopentasiloxane	Rabbit	No significant irritation

**Skin Sensitisation**

Name	Species	Value
Distillates (petroleum), hydrotreated light	Guinea pig	Not sensitising
Distillates (petroleum), solvent-refined heavy paraffinic	Guinea pig	Not sensitising
Glycerin	Guinea pig	Not sensitising
Decamethylcyclopentasiloxane	Mouse	Not sensitising

**Respiratory Sensitisation**

For the component/components, either no data is currently available or the data is not sufficient for classification.

**Germ Cell Mutagenicity**

Name	Route	Value
Distillates (petroleum), hydrotreated light	In Vitro	Not mutagenic
Aluminium Oxide (non-fibrous)	In Vitro	Not mutagenic
Distillates (petroleum), solvent-refined heavy paraffinic	In Vitro	Some positive data exist, but the data are not sufficient for classification
Decamethylcyclopentasiloxane	In Vitro	Not mutagenic
Decamethylcyclopentasiloxane	In vivo	Not mutagenic

**Carcinogenicity**

Name	Route	Species	Value
Distillates (petroleum), hydrotreated light	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Aluminium Oxide (non-fibrous)	Inhalation	Rat	Not carcinogenic
Distillates (petroleum), solvent-refined heavy paraffinic	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Glycerin	Ingestion	Mouse	Some positive data exist, but the data are not sufficient for classification
Decamethylcyclopentasiloxane	Inhalation	Rat	Some positive data exist, but the data are not sufficient for classification

**Reproductive Toxicity****Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to female reproduction	Rat	NOAEL 1,000 mg/kg/day	pre mating & during gestation
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to male reproduction	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	Not toxic to development	Rat	NOAEL	pre mating &



**3M Perfect-It III 50383 Ultrafina SE**

				1,000 mg/kg/day	during gestation
Glycerin	Ingestion	Not toxic to female reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not toxic to male reproduction	Rat	NOAEL 2,000 mg/kg/day	2 generation
Glycerin	Ingestion	Not toxic to development	Rat	NOAEL 2,000 mg/kg/day	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not toxic to reproduction and/or development	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not toxic to female reproduction	Rat	NOAEL 2.43 mg/l	2 generation
Decamethylcyclopentasiloxane	Inhalation	Not toxic to male reproduction	Rat	NOAEL 2.43 mg/l	2 generation

**Target Organ(s)**
**Specific Target Organ Toxicity - single exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Distillates (petroleum), hydrotreated light	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), hydrotreated light	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Distillates (petroleum), hydrotreated light	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	
Distillates (petroleum), solvent-refined heavy paraffinic	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human and animal	NOAEL Not available	
Distillates (petroleum), solvent-refined heavy paraffinic	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Professional judgement	NOAEL Not available	

**Specific Target Organ Toxicity - repeated exposure**

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Dodecamethylcyclohexasiloxane	Ingestion	endocrine system   liver   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	28 days
Dodecamethylcyclohexasiloxane	Ingestion	nervous system	All data are negative	Rat	NOAEL 1,000 mg/kg/day	28 days
Aluminium Oxide (non-fibrous)	Inhalation	pneumoconiosis   pulmonary fibrosis	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	occupational exposure
Distillates (petroleum), solvent-refined heavy paraffinic	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 0.21 mg/l	28 days
Glycerin	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Inhalation	heart   liver   kidney and/or bladder	All data are negative	Rat	NOAEL 3.91 mg/l	14 days
Glycerin	Ingestion	endocrine system   hematopoietic system   liver   kidney and/or bladder	All data are negative	Rat	NOAEL 10,000 mg/kg/day	2 years

**3M Perfect-It III 50383 Ultrafina SE**

Decamethylcyclopentasiloxane	Dermal	hematopoietic system   eyes	All data are negative	Rat	NOAEL 1,600 mg/kg/day	28 days
Decamethylcyclopentasiloxane	Inhalation	hematopoietic system   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 2.42 mg/l	2 years
Decamethylcyclopentasiloxane	Inhalation	liver   eyes   kidney and/or bladder	All data are negative	Rat	NOAEL 2.42 mg/l	2 years
Decamethylcyclopentasiloxane	Ingestion	liver   immune system   respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 1,000 mg/kg/day	90 days
Decamethylcyclopentasiloxane	Ingestion	heart   hematopoietic system   kidney and/or bladder	All data are negative	Rat	NOAEL 1,000 mg/kg/day	90 days

**Aspiration Hazard**

Name	Value
Distillates (petroleum), hydrotreated light	Aspiration hazard
Distillates (petroleum), solvent-refined heavy paraffinic	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

**SECTION 12: Ecological information**

The information below may not agree with the EU material classification in Section 2 and/or the ingredient classifications in Section 3 if specific ingredient classifications are mandated by a competent authority. In addition, statements and data presented in Section 12 are based on UN GHS calculation rules and classifications derived from 3M assessments.

**12.1. Toxicity**

No product test data available.

Material	CAS Nbr	Organism	Type	Exposure	Test endpoint	Test result
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Water flea	Experimental	48 hours	EC50	4.4 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Algae	Experimental	72 hours	EC50	0.15 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Rainbow trout	Experimental	96 hours	LC50	1.6 mg/l
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Crustacea	Experimental	48 hours	EC50	0.062 mg/l
Glycerin	56-81-5	Water flea	Experimental	24 hours	EC50	>10,000 mg/l
Glycerin	56-81-5	Goldfish	Experimental	24 hours	LC50	>5,000 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Water flea	Experimental	48 hours	EC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Fish	Experimental	96 hours	LC50	>100 mg/l
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	EC50	>100 mg/l

**3M Perfect-It III 50383 Ultrafina SE**

fibrous)						
Aluminium Oxide (non-fibrous)	1344-28-1	Green algae	Experimental	72 hours	NOEC	>100 mg/l
Decamethylcyclopentasiloxane	541-02-6		Data not available or insufficient for classification			
Dodecamethylcyclohexasiloxane	540-97-6		Data not available or insufficient for classification			
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4		Data not available or insufficient for classification			

**12.2. Persistence and degradability**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Biodegradation	28 days	BOD	0 % weight	OECD 301C - MITI test (I)
Dodecamethylcyclohexasiloxane	540-97-6	Experimental Biodegradation	28 days	CO2 evolution	4.46 % weight	Other methods
Decamethylcyclopentasiloxane	541-02-6	Experimental Biodegradation	28 days	Percent degraded	0.14 % weight	Other methods
Glycerin	56-81-5	Experimental Biodegradation	14 days	BOD	63 % weight	OECD 301C - MITI test (I)
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.3 : Bioaccumulative potential**

Material	CAS Nbr	Test type	Duration	Study Type	Test result	Protocol
Aluminium Oxide (non-fibrous)	1344-28-1	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
1,2-Benzisothiazol-3(2H)-one	2634-33-5	Experimental Bioconcentration		Log Kow	1.45	Other methods

**3M Perfect-It III 50383 Ultrafina SE**

Dodecamethylcyclohexasiloxane	540-97-6	Experimental BCF - Fathead Mi	49 days	Bioaccumulation factor	1160	OECD 305E - Bioaccumulation flow-through fish test
Decamethylcyclopentasiloxane	541-02-6	Experimental BCF - Fathead Mi	105 days	Bioaccumulation factor	13300	Other methods
Glycerin	56-81-5	Experimental Bioconcentration		Log Kow	-1.76	Other methods
Distillates (petroleum), solvent-refined heavy paraffinic	64741-88-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Distillates (petroleum), hydrotreated light	64742-47-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

**12.4. Mobility in soil**

Please contact manufacturer for more details

**12.5. Results of the PBT and vPvB assessment**

No information available at this time, contact manufacturer for more details

**12.6. Other adverse effects**

No information available.

**SECTION 13: Disposal considerations****13.1 Waste treatment methods**

See Section 11.1 Information on toxicological effects

Incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. As a disposal alternative, utilize an acceptable permitted waste disposal facility. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

The coding of a waste stream is based on the application of the product by the consumer. Since this is out of the control of 3M, no waste code(s) for products after use will be provided. Please refer to the European Waste Code (EWC - 2000/532/EC and amendments) to assign the correct waste code to your waste stream. Ensure national and/or regional regulations are complied with and always use a licensed waste contractor.

**EU waste code (product as sold)**

08 01 11\* Waste paint and varnish containing organic solvents or other dangerous substances

**SECTION 14: Transportation information**

GC-8010-3469-2, GC-8010-3470-0, UU-0016-6332-5, UU-0016-6334-1

Not hazardous for transportation

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### Global inventory status

Contact 3M for more information. The components of this material are in compliance with the provisions of the Korea Chemical Control Act. Certain restrictions may apply. Contact the selling division for additional information. The components of this material are in compliance with the provisions of Australia National Industrial Chemical Notification and Assessment Scheme (NICNAS). Certain restrictions may apply. Contact the selling division for additional information. The components of this product are in compliance with the new substance notification requirements of CEPA. The components of this product are in compliance with the chemical notification requirements of TSCA. This product complies with Measures on Environmental Management of New Chemical Substances. All ingredients are listed on or exempt from on China IECSC inventory.

### 15.2. Chemical Safety Assessment

Not applicable

## SECTION 16: Other information

### List of relevant H statements

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
H413	May cause long lasting harmful effects to aquatic life.

### Revision information:

CLP: Ingredient table information was added.

Section 3: Composition/ Information of ingredients table information was modified.

Section 12: Component ecotoxicity information information was modified.

Section 12: Persistence and Degradability information information was modified.

Section 12:Biocumulative potential information information was modified.

DISCLAIMER: The information on this Safety Data Sheet is based on our experience and is correct to the best of our knowledge at the date of publication, but we do not accept any liability for any loss, damage or injury resulting from its use (except as required by law). The information may not be valid for any use not referred to in this Data Sheet or use of the product in combination with other materials. For these reasons, it is important that customers carry out their own test to satisfy themselves as to the suitability of the product for their own intended applications.

3M United Kingdom MSDSs are available at [www.3M.com/uk](http://www.3M.com/uk)