



## SAFETY DATA SHEET BLACK TRIM WAX

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

**Product name** BLACK TRIM WAX

**Product number** BTW375, HBC000, RBW375, PBT375, MBT500, PGT375

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Car maintenance product.

#### 1.3. Details of the supplier of the safety data sheet

**Supplier** TETROSYL LIMITED  
Bury  
Lancashire  
England  
BL9 7NY

0161 764 5981  
0161 797 5899  
info@tetrosyl.com

**Manufacturer** TETROSYL LIMITED  
Bury  
Lancashire  
England  
BL9 7NY

0161 764 5981  
0161 797 5899  
info@tetrosyl.com

#### 1.4. Emergency telephone number

**Emergency telephone** 0161 764 5981

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification (EC 1272/2008)

**Physical hazards** Flam. Liq. 3 - H226

**Health hazards** Not Classified

**Environmental hazards** Not Classified

**Classification (67/548/EEC or 1999/45/EC)** R10.

**Environmental** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

## BLACK TRIM WAX

### 2.2. Label elements

#### Pictogram



#### Signal word

Warning

#### Hazard statements

H226 Flammable liquid and vapour.

#### Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P501 Dispose of contents/ container in accordance with local regulations.

### 2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

<b>HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, &lt;2% AROMATICS</b>			<b>5-10%</b>
CAS number: —	EC number: 919-857-5	REACH registration number: 01-2119463258-33-XXXX	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Flam. Liq. 3 - H226	Xn; R65. R10, R66, R67		
STOT SE 3 - H336			
Asp. Tox. 1 - H304			
<b>AQUEOUS DISPERSION OF PIGMENT BLACK 7</b>			<b>5-10%</b>
CAS number: 1333-86-4			
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Not Classified	-		
<b>PARAFFIN WAX</b>			<b>1-5%</b>
CAS number: 8002-74-2	EC number: 232-315-6	REACH registration number: 01-2119488076-30-0007	
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Not Classified	-		
<b>DIPHENYL OXIDE</b>			<b>&lt;1%</b>
CAS number: 101-84-8			
EC number: 202-981-2			
<b>Classification</b>	<b>Classification (67/548/EEC or 1999/45/EC)</b>		
Eye Irrit. 2 - H319	N;R51/53.		
Aquatic Chronic 2 - H411			

## BLACK TRIM WAX

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

<b>General information</b>	Remove affected person from source of contamination. Effects may be delayed. Keep affected person under observation. Get medical attention. CAUTION! First aid personnel must be aware of own risk during rescue! Move affected person to fresh air at once. Keep affected person away from heat, sparks and flames. If breathing stops, provide artificial respiration. Place unconscious person on the side in the recovery position and ensure breathing can take place.
<b>Inhalation</b>	Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Keep affected person under observation. Get medical attention. Show this Safety Data Sheet to the medical personnel. Place unconscious person on their side in the recovery position and ensure breathing can take place. If breathing stops, provide artificial respiration.
<b>Ingestion</b>	Get medical attention immediately. Rinse mouth thoroughly with water. Give plenty of water to drink. Give milk instead of water if readily available. Keep affected person under observation. Do not induce vomiting. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention immediately. Show this Safety Data Sheet to the medical personnel. Never give anything by mouth to an unconscious person. Keep affected person away from heat, sparks and flames. Place unconscious person on their side in the recovery position and ensure breathing can take place.
<b>Skin contact</b>	Remove contaminated clothing immediately and wash skin with soap and water. Consult a physician for specific advice.
<b>Eye contact</b>	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Do not rub eye. Get medical attention if any discomfort continues.

#### 4.2. Most important symptoms and effects, both acute and delayed

<b>General information</b>	The severity of the symptoms described will vary dependent on the concentration and the length of exposure. Effects may be delayed. Keep affected person under observation.
<b>Inhalation</b>	In case of overexposure, organic solvents may depress the central nervous system causing dizziness and intoxication, and at very high concentrations unconsciousness and death. Vapours may cause headache, fatigue, dizziness and nausea. Vapours in high concentrations are anaesthetic. Symptoms following overexposure may include the following: Headache. Fatigue. Dizziness. Central nervous system depression.
<b>Ingestion</b>	May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication. May cause chemical burns in mouth and throat. Central nervous system depression. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.
<b>Skin contact</b>	Prolonged contact may cause redness, irritation and dry skin.
<b>Eye contact</b>	Irritation, burning, lachrymation, blurred vision after liquid splash.

#### 4.3. Indication of any immediate medical attention and special treatment needed

<b>Notes for the doctor</b>	No specific recommendations. If in doubt, get medical attention promptly.
-----------------------------	---

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

## BLACK TRIM WAX

**Suitable extinguishing media** Extinguish with the following media: Foam, carbon dioxide or dry powder. Water. Use fire-extinguishing media suitable for the surrounding fire.

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

### 5.2. Special hazards arising from the substance or mixture

**Specific hazards** Vapours may form explosive mixtures with air. Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. The product is highly flammable. Forms explosive mixtures with air. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back.

**Hazardous combustion products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

### 5.3. Advice for firefighters

**Protective actions during firefighting** Avoid breathing fire gases or vapours. Keep up-wind to avoid fumes. Risk of re-ignition after fire has been extinguished. Risk of explosion. Cool containers exposed to flames with water until well after the fire is out. Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material.

**Special protective equipment for firefighters** Leave danger zone immediately.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**Personal precautions** Wear protective clothing as described in Section 8 of this safety data sheet. Use suitable respiratory protection if ventilation is inadequate. Take precautionary measures against static discharges. No smoking, sparks, flames or other sources of ignition near spillage. Do not breathe vapour. Avoid contact with skin and eyes. In case of spills, beware of slippery floors and surfaces.

### 6.2. Environmental precautions

**Environmental precautions** Do not discharge into drains or watercourses or onto the ground. Avoid the spillage or runoff entering drains, sewers or watercourses. Avoid discharge to the aquatic environment.

### 6.3. Methods and material for containment and cleaning up

**Methods for cleaning up** For waste disposal, see Section 13. Stop leak if possible without risk. Absorb spillage with non-combustible, absorbent material. Collect and place in suitable waste disposal containers and seal securely. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Provide adequate ventilation. Contain spillage with sand, earth or other suitable non-combustible material. Avoid the spillage or runoff entering drains, sewers or watercourses. Cover large spillages with alcohol-resistant foam.

### 6.4. Reference to other sections

**Reference to other sections** Wear protective clothing as described in Section 8 of this safety data sheet. For waste disposal, see section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

## BLACK TRIM WAX

### Usage precautions

Read and follow manufacturer's recommendations. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. Vapours may accumulate on the floor and in low-lying areas. Static electricity and formation of sparks must be prevented. Do not eat, drink or smoke when using the product. Avoid inhalation of vapours/spray and contact with skin and eyes. Good personal hygiene procedures should be implemented. Provide adequate ventilation. Avoid inhalation of vapours. Use approved respirator if air contamination is above an acceptable level. Mechanical ventilation or local exhaust ventilation may be required.

### 7.2. Conditions for safe storage, including any incompatibilities

#### Storage precautions

Keep away from heat, sparks and open flame. Keep container tightly closed. Keep containers upright. Keep only in the original container. Avoid contact with oxidising agents. Do not store near heat sources or expose to high temperatures. Store away from the following materials: Oxidising materials.

#### Storage class

Flammable liquid storage.

### 7.3. Specific end use(s)

#### Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

## SECTION 8: Exposure Controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

#### AQUEOUS DISPERSION OF PIGMENT BLACK 7

Long-term exposure limit (8-hour TWA): WEL 3.5 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): WEL 7 mg/m<sup>3</sup>

#### PARAFFIN WAX

Long-term exposure limit (8-hour TWA): WEL 2 mg/m<sup>3</sup> fume

Short-term exposure limit (15-minute): WEL 6 mg/m<sup>3</sup> fume

#### DIPHENYL OXIDE

Long-term exposure limit (8-hour TWA): WEL 1 ppm 7.1 mg/m<sup>3</sup> vapour

WEL = Workplace Exposure Limit

### 8.2. Exposure controls

#### Protective equipment



#### Appropriate engineering controls

Use explosion-proof general and local exhaust ventilation. Avoid inhalation of vapours. Observe any occupational exposure limits for the product or ingredients. All handling should only take place in well-ventilated areas.

#### Eye/face protection

Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible. Unless the assessment indicates a higher degree of protection is required, the following protection should be worn: Tight-fitting safety glasses.

#### Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. Frequent changes are recommended.

#### Other skin and body protection

Wear suitable protective clothing as protection against splashing or contamination.

## BLACK TRIM WAX

<b>Hygiene measures</b>	Provide eyewash station. Wash promptly with soap and water if skin becomes contaminated. When using do not eat, drink or smoke. Contaminated clothing should be placed in a closed container for disposal or decontamination.
<b>Respiratory protection</b>	If ventilation is inadequate, suitable respiratory protection must be worn. Check that the respirator fits tightly and the filter is changed regularly. Wear a respirator fitted with the following cartridge: Gas filter, type AX.

### SECTION 9: Physical and Chemical Properties

#### 9.1. Information on basic physical and chemical properties

<b>Appearance</b>	Viscous liquid.
<b>Colour</b>	Black.
<b>Odour</b>	Perfume.
<b>Odour threshold</b>	Scientifically unjustified. Scientifically unjustified.
<b>pH</b>	pH (concentrated solution): 7.0 - 9.0
<b>Melting point</b>	Scientifically unjustified.
<b>Initial boiling point and range</b>	100°C @
<b>Flash point</b>	40°C
<b>Evaporation rate</b>	Scientifically unjustified.
<b>Upper/lower flammability or explosive limits</b>	Scientifically unjustified.
<b>Vapour pressure</b>	Scientifically unjustified.
<b>Vapour density</b>	Scientifically unjustified.
<b>Relative density</b>	0.955 - 0.975 @ 20°C
<b>Solubility(ies)</b>	Slightly soluble in water.
<b>Partition coefficient</b>	Scientifically unjustified.
<b>Auto-ignition temperature</b>	Scientifically unjustified.
<b>Decomposition Temperature</b>	Scientifically unjustified.
<b>Viscosity</b>	800 - 2000 cP @ 20°C
<b>Oxidising properties</b>	Not determined.

#### 9.2. Other information

<b>Other information</b>	None.
--------------------------	-------

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

<b>Reactivity</b>	There are no known reactivity hazards associated with this product.
-------------------	---

#### 10.2. Chemical stability

<b>Stability</b>	Stable at normal ambient temperatures and when used as recommended.
------------------	---

#### 10.3. Possibility of hazardous reactions

<b>Possibility of hazardous reactions</b>	Not relevant.
---	---------------

## BLACK TRIM WAX

### 10.4. Conditions to avoid

**Conditions to avoid** Avoid heat, flames and other sources of ignition.

### 10.5. Incompatible materials

**Materials to avoid** No specific material or group of materials is likely to react with the product to produce a hazardous situation.

### 10.6. Hazardous decomposition products

**Hazardous decomposition products** Oxides of carbon. Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

<b>General information</b>	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. The product contains small amounts of organic solvents. Extensive use of the product in areas with inadequate ventilation may result in the accumulation of hazardous vapour concentrations.
<b>Inhalation</b>	Vapour may irritate respiratory system/lungs.
<b>Ingestion</b>	Pneumonia may be the result if vomited material containing solvents reaches the lungs.
<b>Skin contact</b>	Repeated exposure may cause skin dryness or cracking.
<b>Eye contact</b>	Irritating to eyes. Symptoms following overexposure may include the following: Redness. Pain. Vapour or spray in the eyes may cause irritation and smarting.
<b>Acute and chronic health hazards</b>	This chemical can be hazardous when inhaled and/or touched. May cause severe internal injury. Vapour from this product may be hazardous by inhalation.
<b>Route of entry</b>	Inhalation Ingestion. Skin and/or eye contact Skin absorption
<b>Target organs</b>	Skin Central nervous system Eyes Respiratory system, lungs
<b>Medical symptoms</b>	Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo.
<b>Medical considerations</b>	Skin disorders and allergies.

## SECTION 12: Ecological Information

**Ecotoxicity** The product contains a substance which is harmful to aquatic organisms and which may cause long-term adverse effects in the aquatic environment.

### 12.1. Toxicity

**Acute toxicity - fish** LC<sub>50</sub>, 96 hours: 1-10 mg/l, Fish

### 12.2. Persistence and degradability

**Persistence and degradability** No data available.

### 12.3. Bioaccumulative potential

**Bioaccumulative potential** No data available on bioaccumulation.

**Partition coefficient** Scientifically unjustified.

### 12.4. Mobility in soil

**Mobility** The product is partly miscible with water and may spread in the aquatic environment.

## BLACK TRIM WAX

**Adsorption/desorption coefficient** Not available.

### 12.5. Results of PBT and vPvB assessment

**Results of PBT and vPvB assessment** This substance is not classified as PBT or vPvB according to current EU criteria.

### 12.6. Other adverse effects

**Other adverse effects** Not available.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

**General information** Waste is classified as hazardous waste. Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Do not puncture or incinerate, even when empty.

**Disposal methods** Confirm disposal procedures with environmental engineer and local regulations. Containers should be thoroughly emptied before disposal because of the risk of an explosion. Empty containers must not be punctured or incinerated because of the risk of an explosion. Reuse or recycle products wherever possible.

## SECTION 14: Transport information

### 14.1. UN number

<b>UN No. (ADR/RID)</b>	1993
<b>UN No. (IMDG)</b>	1993
<b>UN No. (ICAO)</b>	1993
<b>UN No. (ADN)</b>	1993

### 14.2. UN proper shipping name

<b>Proper shipping name (ADR/RID)</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ACETIC ACID ...%)
<b>Proper shipping name (IMDG)</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ACETIC ACID ...%)
<b>Proper shipping name (ICAO)</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ACETIC ACID ...%)
<b>Proper shipping name (ADN)</b>	FLAMMABLE LIQUID, N.O.S. (CONTAINS HYDROCARBONS, C9 - C11, n-ALKANES, ISOALKANES, CYCLICS, <2% AROMATICS, ACETIC ACID ...%)

### 14.3. Transport hazard class(es)

<b>ADR/RID class</b>	3
<b>ADR/RID classification code</b>	F1
<b>ADR/RID label</b>	3
<b>IMDG class</b>	3
<b>ICAO class/division</b>	3
<b>ADN class</b>	3



## BLACK TRIM WAX

### Transport labels



#### 14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

#### 14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

#### 14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3Y
Hazard Identification Number (ADR/RID)	30
Tunnel restriction code	(D/E)

#### 14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### SECTION 15: Regulatory information

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU legislation Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

#### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

### SECTION 16: Other information

Revision comments	NOTE: Lines within the margin indicate significant changes from the previous revision.
Revision date	12/04/2016
Revision	20
Supersedes date	31/07/2015
SDS status	Approved.

## BLACK TRIM WAX

### **Risk phrases in full**

R10 Flammable.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

### **Hazard statements in full**

H226 Flammable liquid and vapour.  
H304 May be fatal if swallowed and enters airways.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.