

FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

Page: 1

Compilation date: 29/04/2010

**Revision date:** 16/04/2015

Revision No: 3

## Section 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Product name: FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

Product code: 7163

# 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: PC31: Polishes and wax blends.

### 1.3. Details of the supplier of the safety data sheet

Company name: Farecla Products Limited

Broadmeads Ware Hertfordshire SG12 9HS

UK

**Tel:** +44 (0)1920 465041

Fax: +44 (0)1920 466557

Email: technical@farecla.com

## 1.4. Emergency telephone number

Emergency tel: +44 (0)1920 465041

(office hours only)

## Section 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification under CLP: -: EUH208

Most important adverse effects: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

# 2.2. Label elements

Label elements:

Hazard statements: EUH208: Contains 1,2-benzisothiazolin-3-one. May produce an allergic reaction.

**Precautionary statements:** P102: Keep out of reach of children.

P233: Keep container tightly closed.

### 2.3. Other hazards

**PBT:** This product is not identified as a PBT/vPvB substance.

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

**Page:** 2

1-10%

## Section 3: Composition/information on ingredients

## 3.2. Mixtures

# Hazardous ingredients:

ALUMINIUM OXIDE 1 - REACH registered number(s): 01-2119529248-35-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
215-691-6	1344-28-1	Substance with a Community	-	30-50%
		workplace exposure limit.		

HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS - REACH registered number (s): 01-2119456620-43-XXXX

926-141-6	-	-	Asp. Tox. 1: H304; -: EUH066	10-30%	
WHITE MINERAL OIL (PETROLEUM) - REACH registered number(s): 01-2119487078-27-XXXX					

 232-455-8
 8042-47-5
 Substance with a Community
 Asp. Tox. 1: H304

		workplace exposure limit.		
CALCINED CHINA CLAY				

296-473-8	92704-41-1	Substance with a Community	-	1-10%	
		workplace exposure limit.			

### Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Wash immediately with plenty of soap and water.

**Eye contact:** Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water.

Inhalation: Consult a doctor.

## 4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

**Eye contact:** There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No symptoms.

Delayed / immediate effects: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

### Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used.

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

### 5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

#### 5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

### Section 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details.

### 6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers.

## 6.3. Methods and material for containment and cleaning up

Clean-up procedures: Wash the spillage site with large amounts of water.

### 6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

### Section 7: Handling and storage

### 7.1. Precautions for safe handling

Handling requirements: Avoid the formation or spread of dust in the air.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area.

Suitable packaging: Must only be kept in original packaging.

7.3. Specific end use(s)

Specific end use(s): No data available.

### Section 8: Exposure controls/personal protection

8.1. Control parameters

### Hazardous ingredients:

#### ALUMINIUM OXIDE 1

#### Workplace exposure limits:

#### **Respirable dust**

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	-	-	5mg/m3	-

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

# HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

EU	1200mg/m3, 165ppm	-	-	-	
WHITE MINE	RAL OIL (PETROLEUM)				
EU	5 mg/m3	-	-	-	
CALCINED CHINA CLAY					
EU	-	-	2.0 mg/m3	-	

# **DNEL/PNEC** Values

**DNEL / PNEC** No data available.

## 8.2. Exposure controls

Engineering measures: Not applicable.

Respiratory protection: Respiratory protection not required.

Hand protection: Protective gloves.

Eye protection: Safety glasses.

Skin protection: Protective clothing.

Environmental: No special requirement.

## Section 9: Physical and chemical properties

## 9.1. Information on basic physical and chemical properties

State:	Paste		
Colour:	White		
Odour:	Characteristic odour		
Evaporation rate:	Negligible		
Oxidising:	Non-oxidising (by EC criteria)		
Solubility in water:	Miscible in all proportions		
Also soluble in:	Not Available		
Viscosity:	Viscous		
Kinematic viscosity:	25000		
Viscosity test method:	Brookfield @ 20degC		
Boiling point/range°C:	Not Available	Melting point/range°C:	Not Available
Flammability limits %: lower:	Not Available	upper:	Not Available
Flash point°C:	>93	Part.coeff. n-octanol/water:	Not Available
Autoflammability°C:	>200	Vapour pressure:	Not Available
Relative density:	1.45	pH:	8.8
VOC g/l:	156		

9.2. Other information

Other information: Not applicable.

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

### Section 10: Stability and reactivity

### 10.1. Reactivity

#### Reactivity: Stable under recommended transport or storage conditions.

#### 10.2. Chemical stability

Chemical stability: Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

### 10.4. Conditions to avoid

Conditions to avoid: Heat.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

### **10.6. Hazardous decomposition products**

Haz. decomp. products: In combustion emits toxic fumes.

### Section 11: Toxicological information

## 11.1. Information on toxicological effects

#### Hazardous ingredients:

**ALUMINIUM OXIDE 1** 

DUST/MIST	RAT	LC50	7.6	mg/l
ORAL	RAT	LD50	> 2000	mg/kg

### HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

DERMAL	RBT	LD50	> 5000	mg/kg
ORAL	RAT	LD50	> 5000	mg/kg
VAPOURS	RAT	8H LC50	> 5000	mg/l

Toxicity values: No data available.

### Symptoms / routes of exposure

Skin contact:There may be mild irritation at the site of contact.Eye contact:There may be irritation and redness.Ingestion:There may be irritation of the throat.Inhalation:No symptoms.Delayed / immediate effects:No data available.Other information:Not applicable.

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

Page: 6

## Section 12: Ecological information

## 12.1. Toxicity

## Hazardous ingredients:

### **ALUMINIUM OXIDE 1**

Daphnia magna	48H EC50	> 100	mg/l
GREEN ALGA (Selenastrum capricornutum)	48H EC50	> 100	mg/l
Salmo trutta	96H LC50	> 100	mg/l

## HYDROCARBONS, C11-C14, N-ALKANES, ISOALKANES, CYCLICS, < 2% AROMATICS

Daphnia magna	48H EC50	1000	mg/l
Pseudokirchneriella subcapitata	72H ErC50	1000	mg/l
RAINBOW TROUT (Oncorhynchus mykiss)	96H LC50	1000	mg/l

### **CALCINED CHINA CLAY**

ALGAE	72H IC50	>100	mg/l
DAPHNIA	48H EC50	>1	mg/l
FISH	96H LC50	>100	mg/l

## 12.2. Persistence and degradability

Persistence and degradability: Biodegradable. More than 80% biodegradable according to OECD 301 (calculated).

### 12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility: No data available.

## 12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

### Section 13: Disposal considerations

## 13.1. Waste treatment methods

Disposal operations:	Transfer to a suitable container and arrange for collection by specialised disposal
	company.
<b>Recovery operations:</b>	Not applicable.
Waste code number:	08 04 12
Disposal of packaging:	Not applicable.
NB:	The user's attention is drawn to the possible existence of regional or national
	regulations regarding disposal.

# FARECLA G3 PROFESSIONAL SCRATCH REMOVER PASTE

## Section 14: Transport information

### **Transport class:** This product does not require a classification for transport.

# Section 15: Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

# 15.2. Chemical Safety Assessment

**Chemical safety assessment:** A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

## Section 16: Other information

## Other information

Other information:	This safety data sheet is prepared in accordance with Commission Regulation (EU) No
	453/2010.
	* indicates text in the SDS which has changed since the last revision.
Phrases used in s.2 and s.3:	EUH066: Repeated exposure may cause skin dryness or cracking.
	EUH208: Contains <name of="" sensitising="" substance="">. May produce an allergic reaction.</name>
	H304: May be fatal if swallowed and enters airways.
Legal disclaimer:	The above information is believed to be correct but does not purport to be all inclusive
	and shall be used only as a guide. This company shall not be held liable for any
	damage resulting from handling or from contact with the above product.