

**W.A.C.  
PRODUCTS**

**TAR AND GLUE REMOVER**

For the  
Professional  
finish!

**Details of the supplier of the safety data sheet**

**Wholesale Automotive UK**

Unit 18 Upminster Trading Park

Warley Street

Upminster

Essex

RM14 3PJ

United Kingdom

t : 01708 726 995

## **TG**

### **Product Description**

A powerful solvent which quickly removes residues of most types of adhesives and sealants used in the motor industry. Formulated to have the minimum effect on paint-work and upholstery materials. A most effective tar remover for wheels and body-work.

### **Directions**

Apply with a clean soft cloth and rub gently until the residue is dispersed and removed. If in doubt that a surface will stand solvent cleaning, make a test on a small hidden area before use.

Avoid over application and soaking, which might soften some materials.

### **Health and Safety**

HARMFUL

U.N. Number 1993

R65 Harmful: may cause lung damage if swallowed.

R10 Flammable.

S51 Use only in well ventilated areas.

S24/25 Avoid contact with skin and eyes.

S62 If swallowed do not induce vomiting. Seek medical advice immediately and show this container or label.

S2 Keep out of reach of children.

## PRODUCT SAFETY DATA SHEET

### (1) IDENTIFICATION :

Product name : TAR & GLUE REMOVER

Description: Tar & Glue Remover

Code : TG

#### Details of the supplier of the safety data sheet

**Wholesale Automotive UK**  
Unit 18 Upminster Trading Park  
Warley Street  
Upminster  
Essex  
RM14 3PJ  
United Kingdom  
t : 01708 726 995

### (2) COMPOSITION/INFORMATION ON INGREDIENTS

Hydrocarbon solvent	80-100%
---------------------	---------

### (3) HAZARDS IDENTIFICATION

EYE CONTACT : Will cause irritation.

SKIN CONTACT : Prolonged or repeated contact may cause irritation and dryness.

CONTACT WITH RESPIRATORY SYSTEM : Not a hazard in normal use. Excessive exposure may cause irritation of the respiratory tract, headache, dizziness and nausea.

FLAMMABILITY : Flammable

OTHER : Not applicable.

### (4) FIRST AID MEASURES

EYE CONTACT : Immediately flush eyes with water, holding eyelids apart, for at least 10 minutes. Seek medical assistance at once.

SKIN CONTACT : Remove contaminated clothing. Wash skin using a proprietary skin cleanser.

INHALATION : In case of overexposure remove to fresh air, keep warm and at rest. Seek medical attention immediately.

INGESTION : Do not induce vomiting. Give 200-300 ml of water to drink and seek medical assistance immediately.

### (5) FIRE FIGHTING MEASURES

Use foam, dry powder or CO<sub>2</sub>

### (6) ACCIDENTAL RELEASE

Take the necessary precautions to prevent contact. Shut off leaks if this can be done without personal risk. Contain the spillage if possible. Keep the area clear. Absorb using sand or other inert material and transfer to suitable containers for disposal.

Observe Local Authority regulations.

### (7) HANDLING & STORAGE

Store in a cool, dry place, protected from frost and away from acids, strong oxidising agents and sources of ignition.

### (8) EXPOSURE CONTROLS/PERSONAL PROTECTION

EYE PROTECTION : Wear eye protection if splashing is likely.

HAND PROTECTION : Wear impervious gloves.

BODY PROTECTION : As necessary to prevent contact.

RESPIRATORY PROTECTION : Not a hazard in normal use. Use in a well ventilated area with properly adjusted equipment.

Avoid breathing vapour/spray.

OTHER PROTECTIVE MEASURES : Not applicable.

### (9) PHYSICAL & CHEMICAL PROPERTIES

Appearance : Colourless liquid.

Odour : Solvent.

pH 1% in water (typical) : Not applicable.

Boiling point : 154°C

Melting point : Not applicable.

Flash point : 43°C.

Auto-ignition temp.: 465°C.

Explosive properties : Not applicable.

Oxidising properties : None.

Vapour pressure : 5 mm Hg at 20 °C

Relative density at 20 °C (typical) : 0.875

Solubility : Immiscible with water.

Viscosity : Free flowing.

### (10) STABILITY AND REACTIVITY

Hazardous reactions : Incompatible with strong oxidising agents and acids.

Hazardous decomposition products : None known.

Hazardous polymerisation : Will not occur.

Stability : Stable.

### (11) TOXICOLOGICAL INFORMATION

Eye contact : Will cause irritation.

Skin contact : Prolonged or repeated contact may cause irritation and dryness.

Inhalation : Breathing vapour/spray mist may cause irritation of the respiratory tract, headache, dizziness and nausea.

Ingestion : Low toxicity. Will cause irritation of gastrointestinal tract.

Long term : Based on current knowledge, no long term effects are anticipated if used correctly.

### (12) ECOLOGICAL INFORMATION

Do not allow this product to enter water courses untreated.

### (13) DISPOSAL

Consult national and local regulations. Dispose via a reputable chemical waste contractor.

### (14) TRANSPORT INFORMATION

UN Number 1993 for transport. Class 3.

Transport Category 3.

### (15) REGULATORY INFORMATION

Occupational exposure limits : Hydrocarbon solvent 50ppm  
OES 8 hour TWA.

Xn Harmful

(R10) Flammable

### (16) OTHER INFORMATION

It is for users to satisfy themselves of the suitability of this product for their own applications.

This information is believed to be accurate at the time of printing and is given in good faith.

Date of issue : 1 November, 2013