

Heavy Duty Hoist Rings - Metric

Part No.	Rated Load (kg)	A	B	C	D	E +/- 3.0	F	G	K	L	M	TL (Nm)	Weight (kg)
34212	400	16.5	58.2	24.4	11.1	16	82	M8x1.25	31.8	4	38.5	9.5	0.24
34214	400	16.5	58.2	24.4	11.1	21	82	M8x1.25	31.8	4	38.5	9.5	0.25
34312	450	16.5	58.2	24.4	11.1	16	82	M10x1.5	31.8	4	36.5	16	0.25
34314	450	16.5	58.2	24.4	11.1	26	82	M10x1.5	31.8	4	36.5	16	0.26
34515	1050	25.4	88.9	38.1	19.1	25	134.9	M12x1.75	48	4.4	65	37	0.78
•34505	1050	25.4	88.9	38.1	19.1	25	174.6	M12x1.75	48	4.4	104.7	37	0.93
34516	1050	25.4	88.9	38.1	19.1	32	134.9	M12x1.75	48	4.4	65	37	0.83
•34517	1050	25.4	88.9	38.1	19.1	32	174.6	M12x1.75	48	4.4	101.7	37	0.98
34518	1500	25.4	88.9	38.1	19.1	25	135.2	M14x2.0	48	4.4	65.3	45	0.79
•34519	1500	25.4	88.9	38.1	19.1	25	174.9	M14x2.0	48	4.4	105	45	0.95
34520	1500	25.4	88.9	38.1	19.1	32	135.2	M14x2.0	48	4.4	65.3	45	0.84
•34521	1500	25.4	88.9	38.1	19.1	32	174.9	M14x2.0	48	4.4	105	45	0.98
34614	1900	25.4	88.9	38.1	19.1	25	134.9	M16x2.0	48	4.4	62	80	0.81
•34604	1900	25.4	88.9	38.1	19.1	25	174.6	M16x2.0	48	4.4	101.7	80	0.96
34615	1900	25.4	88.9	38.1	19.1	32	134.9	M16x2.0	48	4.4	62	80	0.85
•34616	1900	25.4	88.9	38.1	19.1	32	174.6	M16x2.0	48	4.4	101.7	80	1
34714	2200	25.4	88.9	38.1	19.1	25	134.6	M20x2.5	48	4.4	58.7	135	0.86
•34715	2200	25.4	88.9	38.1	19.1	25	174.6	M20x2.5	48	4.4	98.4	135	1.01
34716	2200	25.4	88.9	38.1	19.1	38	134.6	M20x2.5	48	4.4	58.7	135	0.92
•34717	2200	25.4	88.9	38.1	19.1	38	174.6	M20x2.5	48	4.4	98.4	135	1.07
34101	3000	35.6	129.5	52.1	25.4	28	187.2	M20x2.5	71.4	4.6	89.7	135	3.14
•34161	3000	35.6	129.5	52.1	25.4	28	228.6	M20x2.5	71.4	4.6	131.1	135	3.47
34102	4200	35.6	129.5	52.1	25.4	28	187.2	M24x3.0	71.4	4.6	85.7	311	3.29
•34162	4200	35.6	129.5	52.1	25.4	28	228.6	M24x3.0	71.4	4.6	127.1	311	3.62
34103	4200	35.6	129.5	52.1	25.4	38	187.2	M24x3.0	71.4	4.6	85.7	311	3.3
•34163	4200	35.6	129.5	52.1	25.4	38	228.6	M24x3.0	71.4	4.6	127.1	311	3.63
34105	4500	35.6	129.5	52.1	25.4	38	187.2	M30x3.5	71.4	4.6	79.7	311	3.44
•34165	4500	35.6	129.5	52.1	25.4	38	228.6	M30x3.5	71.4	4.6	79.7	311	3.55
34107	4500	35.6	129.5	52.1	25.4	48	187.2	M30x3.5	71.4	4.6	79.7	311	3.55
•34167	4500	35.6	129.5	52.1	25.4	48	228.6	M30x3.5	71.4	4.6	121.1	311	3.88
34401	7000	50.8	171.5	72.9	31.8	67	234.2	M30x3.5	98.5	8.2	95	637.2	7.26
34402	11000	50.8	171.5	72.9	31.8	67	234.2	M36x4.0	98.5	8.2	88.6	1085.5	8.21
†34403	12500	50.8	171.5	72.9	31.8	80	234.2	M42x4.5	98.5	8.2	88.6	1085.5	10.14
†34404	13500	50.8	171.5	72.9	31.8	80	234.2	M48x5.0	98.5	8.2	88.6	1085.5	10.59
†34406	13500	50.8	171.5	72.9	31.8	88	234.2	M56x5.5	98.5	8.2	88.6	1085.5	11.03

NEW ITEMS

34060	25000	69.9	235	100.6	44.5	102	326.6	M64-6.0	131.1	14.7	124.5	3600	25.9
34592	25000	69.9	235	100.6	44.5	102	326.6	M64 x 6.0	131.1	14.7	124.5	76	25.9

* Recommended Torque Load

• Long Bar Models

† Supplied with stud and nut

Note: Dimensions are in millimeters

For Load Ranges up to 113,400 KG.

Heavy Duty® Hoist Rings are completely interchangeable with Safety Engineered Hoist Rings.