

THICKNESS: 0.95 in (24 mm)  
AREAL DENSITY: 3.27 lb/ft<sup>2</sup>

# 3800C



### SHOOTER CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
3800C-SH-MC-L	10.00 x 12.00 in (254 x 305 mm)	2.5 lb (1.1 kg)
3800C-SH-MC-S	8.00 x 10.00 in (203 x 254 mm)	1.6 lb (0.7 kg)

### LE CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
3800C-LE-MC-L	10.00 x 12.00 in (254 x 305 mm)	2.4 lb (1.1 kg)
3800C-LE-MC-S	8.00 x 10.00 in (203 x 254 mm)	1.6 lb (0.7 kg)

### SAPI CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
3800C-SA-MC-XL	11.00 x 14.00 in (279 x 356 mm)	3.3 lb (1.5 kg)
3800C-SA-MC-L	10.25 x 13.25 in (260 x 337 mm)	2.9 lb (1.3 kg)
3800C-SA-MC-M	9.50 x 12.50 in (241 x 318 mm)	2.6 lb (1.1 kg)
3800C-SA-MC-S	8.75 x 11.75 in (222 x 298 mm)	2.2 lb (1.0 kg)

## MODEL 3800C THREAT PERFORMANCE MATRIX

	LEAD CORE		MILD STEEL CORE	
	5.56 x 45 mm - M193 Max. Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max. Velocity 2410 ft/s (735 m/s)	7.62 x 51 mm - M80 Max. Velocity 2810 ft/s (856 m/s)	7.62 x 39 mm - M43 Max. Velocity 2410 ft/s (735 m/s)
3800C-SH-MC-L	6	6	6	6
3800C-SH-MC-S	3	3	3	3
3800C-LE-MC-L	6	6	6	6
3800C-LE-MC-S	3	3	3	3
3800C-SA-MC-XL	6	6	6	6
3800C-SA-MC-L	6	6	6	6
3800C-SA-MC-M	6	6	6	6
3800C-SA-MC-S	3	3	3	3

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

### HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

