

L110

THICKNESS: 0.61 in (16 mm)
AREAL DENSITY: 7.00 lb/ft²



SIDE PLATES - SINGLE CURVE

PART NUMBER	WIDTH x LENGTH	WEIGHT
L110-SP-SC-L	6.00 x 8.00 in (152 x 203 mm)	2.0 lb (1.0 kg)
L110-SP-SC-L	6.00 x 6.00 in (152 x 152 mm)	1.5 lb (0.7 kg)

MODEL L110 THREAT PERFORMANCE MATRIX

	LEAD CORE		MILD STEEL CORE		ENHNC'D PERF	ARMOR PIERCING CORE
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855A1 Max Velocity 3180 ft/s (969 m/s)	7.62 x 39 mm - API Max Velocity 2410 ft/s (735 m/s)
L110-SP-SC-L	1	1	1	1	1	1
L110-SP-SC-S	1	1	1	1	1	1

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

© 2024 Hesco. All rights reserved.

