

THICKNESS: 0.56 in (14 mm)
AREAL DENSITY: 5.68 lb/ft²

U210



SHOOTER CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
U210-SH-MC-L	10.00 x 12.00 in (254 x 305 mm)	3.9 lb (1.8 kg)
U210-SH-MC-S	8.00 x 10.00 in (203 x 254 mm)	2.6 lb (1.2 kg)

SAPI CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
U210-SA-MC-XL	11.00 x 14.00 in (279 x 356 mm)	5.4 lb (2.5 kg)
U210-SA-MC-L	10.25 x 13.25 in (260 x 337 mm)	4.7 lb (2.1 kg)
U210-SA-MC-M	9.50 x 12.50 in (241 x 318 mm)	4.1 lb (1.9 kg)
U210-SA-MC-S	8.75 x 11.75 in (222 x 298 mm)	3.5 lb (1.6 kg)

MODEL U210 THREAT PERFORMANCE MATRIX

	LEAD CORE		MILD STEEL CORE		ENHNC D PERF	ARMOR PIERCING CORE
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)		
U210-SH-MC-L	6	6	6	3	1	
U210-SH-MC-S	6	6	6	1	1	
U210-SA-MC-XL	6	6	6	3	1	
U210-SA-MC-L	6	6	6	3	1	
U210-SA-MC-M	6	6	6	3	1	
U210-SA-MC-S	6	6	6	1	1	

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

