

THICKNESS: 0.85 in (22 mm)
AREAL DENSITY: 4.37 lb/ft²

Z210



SHOOTER CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
Z210-SH-MC-L	10.00 x 12.00 in (254 x 305 mm)	3.1 lb (1.4 kg)
Z210-SH-MC-S	8.00 x 10.00 in (203 x 254 mm)	2.0 lb (0.9 kg)

SAPI CUT - MULTI CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
Z210-SA-MC-XL	11.00 x 14.00 in (279 x 356 mm)	4.3 lb (1.9 kg)
Z210-SA-MC-L	10.25 x 13.25 in (260 x 337 mm)	3.7 lb (1.7 kg)
Z210-SA-MC-M	9.50 x 12.50 in (241 x 318 mm)	3.2 lb (1.5 kg)
Z210-SA-MC-S	8.75 x 11.75 in (222 x 298 mm)	2.8 lb (1.3 kg)

MODEL Z210 THREAT PERFORMANCE MATRIX

	LEAD CORE		MILD STEEL CORE	
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)
Z210-SH-MC-L	6	6	6	6
Z210-SH-MC-S	3	3	3	3
Z210-SA-MC-XL	6	6	6	6
Z210-SA-MC-L	6	6	6	6
Z210-SA-MC-M	6	6	6	6
Z210-SA-MC-S	3	3	3	3

Matrix shows the minimum number of shots that each size plate can be expected to defeat under NIJ testing methods.

HESCO ARMOR, INC.

2210 Port Industrial Road | Aberdeen WA 98520, United States | +1 360 637 6867 | haics@praesidiad.com | hesco.com

