



Riot / Breaching Visor



Gentex TBH Low Cut Helmet with Ops-Core Riot/Breaching Visor

The Ops-Core Riot/Breaching Visor offers modular, rapidly-employed face protection for operators with Ops-Core ARC Rail-equipped helmets. The 3mm thick visor smoothly pivots up and down to provide full face protection as needed. The visor effectively keeps end users safe in riot and breaching operations.

KEY FEATURES

Seamless Integration with Ballistic Helmets

Ops-Core FAST® and Sentry™ helmets, and Gentex ACH/TBH helmets can seamlessly incorporate the Riot Visor, further increasing the scalability by upgrading the protective posture through the addition of the face shield to the helmet.


Stable, Secure Attachment

The Riot/Breaching Visor attaches to rails without tools and creates a seal to the front of the helmet shell. Center of gravity is less of a concern with the Riot/Breaching Visor because the overall system weight is a lot less.

1. Riot Visor assembly fits all sizes of Ops-Core FAST and Sentry helmets, and Gentex ACH/TBH style helmets
2. Ballistic protective lens with hard-coated outside and anti-fog inside
3. Fore/Aft adjustment maintains effective seal with different helmet geometries as well as increases offset to accommodate masks and other equipment as needed
4. Rail interface locking system provides solid platform for the Riot Visor
5. Friction pivot secures Riot Visor at any angle
6. Folding arms for smaller storage footprint
7. Pivots up and down and will remain in set position
8. Riot Visor gasket minimizes the chance that liquids will drip behind the lens
9. Pinlock Anti-Fog Inert (*below, sold separately*) is specifically designed to absorb moisture and prevent fogging while keeping the field of vision clear and the focus on the mission

Product Category	Riot/Breaching Visor
Protection Level	Tested to EN 166:2001 Visor requirements. A steel ball of 6 mm diameter fired at 192m/s
Construction/Materials	High Impact Optical Grade Polycarbonate
Protection Area	62 in ² (400 cm ²)
Viewport Width	15" (38 cm)
Viewport Height	7.5" (19 cm)
Viewport Thickness	0.12" (3 mm)
Weight	1.2 lbs (544.3 g)

Note: All measurements are +/- 3% tolerance



Contact Us

Ops-Core is committed to designing advanced performance capabilities for the elite warrior. For more information regarding the Ops-Core Riot/Breaching Visor, contact Ops-Core at 617.670.3547 or sales@ops-core.com. The Ops-Core Riot/Breaching Visor is controlled for export by the U.S. Export Administration Regulations (EAR) 15 CFR 730-774. The export of this helmet and related technical information requires prior authorization from the U.S. Government.