## 

## **MICROPRISM**

The FAST™ MicroPrism positions Primary Arms® MicroPrism™ optics at a 2.26" optical centerline from the rail. It is also compatible with other optics of industry standard mini-prism footprint (heights may vary depending on the optic). It comes standard with a 2 cross bolt rail clamp but is compatible with the FAST™ QD (Quick Detach) Lever.

FAST™ is a series of optic mounting solutions that provides end users with a quicker sight picture than standard height mounts. FAST™ mounts position most optics at a 2.26″ optical centerline from the rail, which allows for more rapid visual processing of the battlefield by ensuring an ergonomically correct heads-up posture. Further, they provide faster and easier dot/reticle acquisition while wearing night vision goggles, protective masks, plate carriers and other gear.







HEIGHT	COMPATIBILITY	RAIL MOUNT	WEIGHT	COLORS	
2.26" TO OPTICAL CENTERLINE	PRIMARY ARMS® MICOPRISM™ OPTICS AND MOST OPTICS WITH AN INDUSTRY STANDARD MINI-PRISM FOOTPRINT	2 CROSS BOLT RAIL CLAMP, FAST™ QD LEVER COMPATIBLE	OZ: <3.0 G: <85.0	BLACK	FDE
				PART NUMBERS	
MATERIAL	COATING	DIMENSIONS (W X L X H)			
	Committee	Dimensions (if X 2 X ii)		BLACK	FST-MPMB
7075-T6 ALUMINUM	TYPE III HARDCOAT ANODIZED	IN: < 1.8 X 2.2 X 2.1 CM: < 4.6 X 5.6 X 5.3			
ALCOMINO WI				FDE	FST-MPMF





