

IHSL24UL

24VDC Industrial
Slide Gate Operator



DATA SHEET

Key Features

Steel Cabinet	Weatherproof 14 gauge, NEMA 3R steel cabinet
Battery Backup	Yes
Remote Control Access	Security+ 2.0® 3-channel receiver will handle up to 50 remote controls (unlimited remotes with 811LMX/813LMX)
Internet Connectivity	myQ® Facility cloud connection and myQ capability for secure monitoring and control of gate operator from anywhere*
Monitored Safety Devices	6 inputs (main and expansion board)
Solar-Power Capabilities	Yes
Diagnostic Display	LED diagnostic display
Wireless Dual-Gate Communication	Eliminates expensive conduit costs and unsightly driveway scars
Dual-Gate Control	Bi-part delay or synchronized close
Fire Department Compliant	Allows gate to auto open upon loss of AC power or battery depletion; includes manual release
Limit Setting	Electronic
Diagnostic Display	LED diagnostic display
Programmable Auxiliary Relays	4 programmable auxiliary relays accommodate more accessories such as warning lights/alarms
Unauthorized Access Prevention	Can be programmed with anti-tailgate or quick close capabilities
Homelink® Capability	Version 4 or higher

Specifications

Operator Speed	0.5 ft./sec. to 1 ft./sec
Power	120/240VAC single phase, optional 3 phase kit for 208/230/460VAC and 575VAC
Accessory Power	24VDC 1 A max. output; switched and unswitched power
Operator Weight	142 lbs.
Warranty	5 years
Temperature Specification	Without heater -4°F (-20°C) to 140°F (60°C); with optional heater: -40°F (-40°C) to 140°F (60°C)
UL Usage Classification	II, III, IV

Construction

Motor	24VDC brushless motor with soft start/stop
Operator Duty Rating	Continuous-duty
Chassis/Frame	Constructed with 1/4 in. powder coated steel for rust prevention
Gear Reduction	Direct drive 40:1 gear ratio
Cover/Cabinet	Powder-coated, 14 gauge steel cabinet, oil tight, weatherproof NEMA 3R lockable cabinet
Chain	#50
Recommended Capacities	Rated for gates up to 90 ft. in length and weighing up to 5500 lbs.

*When linked with a myQ Facility capable access control. Cellular data or Wi-Fi® connection required

LiftMaster

POWERED BY myQ


IHSL24UL

24VDC Industrial
Slide Gate Operator
Section 32 31 00



DATA SHEET

Dimensions



Capacity

Battery Backup Operation

Battery	Cycles	Standby Time
7Ah	20	105 Days
33Ah	60	180 Days

Recommended Capacity

