

# Freddy Tramp Oil Separator

Leading the way in coolant recycling 

# Freddy®

The Freddy Tramp Oil Separator has been designed to combat the problems associated with tramp oil levels in machine tool coolant systems. Tramp oil can cause a variety of problems, both to the finished product and the operator. The Tramp Oil Separator is easily manoeuvrable, so it can be used throughout the factory and it runs continuously so will not interfere with production, siphoning the tramp oil to the supplied external waste containers and returning the cleaned coolant to the machine tool sump.

- Removes tramp oil from coolants in a variety of applications
- Runs continuously
- Variety of filters and floats available
- Optional UV coolant decontaminator inhibits bacterial growth
- Complete with 24 months warranty

## Specification

- Removes tramp oil from coolants in a variety of applications
- Runs continuously
- Variety of filters and floats available
- Optional UV coolant decontaminator inhibits bacterial growth
- Complete with 24 months warranty



## Freddy Tramp Oil Separator Models

Capacity: 70 litres | Length: 800mm | Width: 516mm | Height: 1185mm

Power unit	# of phases	Weight (empty)	Weight (full)	Airflow	Water flow in *	Water flow out
240v	1	73	143	n/a	4.9 lt/min	2 lt/min
Air	n/a	71	141	33.9	2 - 5 lt/min	2 lt/min

Weight in kilograms (kg)

**LIVETOOLS®**  
Machine Tool People.  
[www.livetools.com.au](http://www.livetools.com.au)

[sales@livetools.com.au](mailto:sales@livetools.com.au)  
02 4017 0198  
115 Young St  
Carrington NSW 2294