

CONNECTION DIAGRAM ACCESSORIES

| | |
|---------------------------|-----------------------------------------|
| MOTOR WINDING THERMOSTATS | |
| CONTACTS _____ @ _____ °C | |
| FIGURE NUMBER _____ | |
| CONTACT RATING | |
| VDLTS | CONTACT RATING CONTINUOUS AMPERES |
| 110-120 | 3.0 |
| 220-240 | 1.5 |
| 440-480 | 0.75 |
| 550-600 | 0.60 |
| | INRUSH AMPERES |
| | 30 |
| | 15 |
| | 7.5 |
| | 6.0 |

| NORMALLY CLOSED | THERMOSTATS | NORMALLY OPEN |
|-----------------|-------------|-----------------|
| <p>FIGURE 1</p> | | <p>FIGURE 4</p> |
| <p>FIGURE 2</p> | | <p>FIGURE 5</p> |
| <p>FIGURE 3</p> | | <p>FIGURE 6</p> |
| <p>FIGURE 7</p> | | <p>FIGURE 8</p> |

CUSTOMER _____ CUSTOMER ORDER NO. _____ S.O. NO. _____

| | | |
|--------------------------|------------------------------|------------------|
| REV. DESC: LOADED TO BUS | | |
| REV. LTR: A | VERSION: 01 | TDR: 00000570390 |
| FILE: \RAG\00013\849 | REVISED: 10:16:21 12/07/2010 | BY: RAGDRF |
| MTL: - | | |

BALDOR

A-C MOTOR CONNECTION ACCESSORIES

SH 1 of 1