



- NOTES:
1. CONNECT LINE LEADS TO L1 AND L2.  
LOW VOLTAGE: CONNECT AS SHOWN.  
HIGH VOLTAGE: MOVE LEAD J TO TERM. 3.  
MOVE LEAD 2 TO TERM. 4.
  2. CONNECTIONS ARE SHOWN FOR STANDARD ROTATION (CCW FACING END OPPOSITE SHAFT EXTENSION). INTERCHANGE LEADS 5 AND 8 TO REVERSE ROTATION.
  3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
  4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE MARKED AS SHOWN.
  5. PILOT CIRCUIT IS CLOSED AT REST.

REV. DESC: OMIT NOTE #6 (SEE ZTR02 NOTES)			
REV. LTR: C	VERSION: 01	TDR: 000000430936	
	FILE: \AAA\00081\292	REVISED: 09:08:49 05/17/2007	
	MTL: -	BY: ENBENBO	

**BALDOR ELECTRIC Co.**

TYPE C, DV, REV, THERMAL (T' STAT IN LINE), TERM PLATE, PILOT

CD0804A01