


| | LINE A | LINE B | JOIN | JOIN | JOIN |
|----------|--------|--------|------|-------|------|
| HIGH STD | 1 | 4 | 2,3 | 8,9 | J,5 |
| HIGH OPP | 1 | 4 | 2,3 | 5,9 | J,8 |
| LOW STD | 1,3 | 4 | 8,9 | 2,J,5 | - |
| LOW OPP | 1,3 | 4 | 5,9 | 2,J,8 | - |

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
3. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

BYPASSING THE HEATER OF A THREE TERMINAL THERMAL



| | | | | | |
|----------------|--|----------------------|--|-------------------------------|--|
| REV. DESC: NEW | | VERSION: 00 | | TDR: 000000360649 | |
| REV. LTR: - | | FILE: \AAA\00126\040 | | REVISED: 10: 27:12 04/18/2005 | |
| CD0016A03 | | MTL: - | | BY: ENJOEPO | |

BALDOR ELECTRIC Co.

TYPE LC, DV, REV,OIL CAP ACR. LINE, 2-TERMINAL THERMAL,8 LDS