



| | LINE A | LINE B | JOIN | JOIN |
|----------|---------|---------|------|------|
| HIGH STD | 1,8 | 4,5 | 2,3 | 6,7 |
| HIGH OPP | 1,5 | 4,8 | 2,3 | 6,7 |
| LOW STD | 1,3,6,8 | 2,4,5,7 | - | - |
| LOW OPP | 1,3,5,7 | 2,4,6,8 | - | - |

NOTES:

1. STANDARD ROTATION IS CCW FACING END OPPOSITE SHAFT EXTENSION.
2. OPTIONAL THERMOSTAT IS PROVIDED WHEN SPECIFIED.
3. OPTIONAL OIL CAP(S) ARE PROVIDED WHEN SPECIFIED. MULTIPLE OIL CAPS ARE CONNECTED IN PARALLEL.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

| | | |
|--------------------------------|----------------------|--------------------------------|
| REV. DESC: ADD OPTIONAL COLORS | | |
| REV. LTR: E | VERSION: 01 | TDR: 00000372126 |
| 9/0000 | FILE: \AAA\00007\419 | REVISED: 15: 44: 39 09/28/2005 |
| | MTL: - | BY: ENJOEPO |

BALDOR ELECTRIC Co.

TYPE L OR LC, DV, REV, SERIES/PAR B PH, 8 LEAD