



NOTES:

1. CONNECT LINE LEADS TO L1 AND L2.  
LOW VOLTAGE: CONNECT AS SHOWN.  
HIGH VOLTAGE: MOVE LEAD J TO TERM. 3.  
MOVE LEAD 2 TO TERM. 4.
2. CONNECTIONS ARE SHOWN FOR STANDARD ROTATION (CCW FACING END OPPOSITE SHAFT EXTENSION). INTERCHANGE LEADS 5 AND 8 TO REVERSE ROTATION.
3. MULTIPLE CAPACITORS ARE CONNECTED IN PARALLEL UNLESS OTHERWISE SPECIFIED.
4. LEAD COLORS ARE OPTIONAL. LEADS MUST ALWAYS BE NUMBERED AS SHOWN.

|   |                      |                                |
|---|----------------------|--------------------------------|
| REV. DESC: REMOVE OPTIONAL THERMAL CONNECTION |                      |                                |
| REV. LTR: H                                   | VERSION: 01          | TDR: 000000373039              |
| ZG00D0  | FILE: \AAA\00007\100 | REVISED: 10: 20: 46 08/11/2005 |
|   | MTL: -               | BY: ENJOEPO                    |

**BALDOR ELECTRIC Co.**

TYPE L, DV, REV, THERMAL, TERMINAL PLATE