

4		3		2		1																			
<div>GENERAL INFORMATION:</div> <div>SHAFT RUNOUT: .001 [.03] T.I.R. PER INCH LENGTH OF EXTENSION</div> <div>END PLAY: .010 TO .063 [.25 TO 1.60]</div> <div>BEARINGS: SLEEVE</div> <div>MOUNTING POSITION: HORIZONTAL</div> <div>ELECTRICAL DATA:</div> <div>OVERLOAD PROTECTOR: AUTOMATIC RESET (T.I. 7AM 036)</div> <div>LEADS: NO. 18 GA., .06 [1.5] THK. PVC 105°C INSUL.</div> <div>GROUND LEAD: NO. 18 GA., .03 [.8] THK. (GREEN/YELLOW) INSUL.</div>				<table><tr><td>REV</td><td>ECO</td><td>REV BY</td><td>DATE</td><td>APPD</td><td>DATE</td></tr><tr><td>C</td><td>0025525</td><td>E.SINECIO</td><td>04-23-2012</td><td>R.RASCON</td><td>04-23-2012</td></tr></table>				REV	ECO	REV BY	DATE	APPD	DATE	C	0025525	E.SINECIO	04-23-2012	R.RASCON	04-23-2012						
REV	ECO	REV BY	DATE	APPD	DATE																				
C	0025525	E.SINECIO	04-23-2012	R.RASCON	04-23-2012																				
<div>NAMEPLATE DATA:</div> <div>MODEL NO.: F48Y98A01</div> <div>CUST. P/N: 493A</div> <div>HP: 1/6,1/10</div> <div>ROT.: CWLE</div> <div>RPM: 1075</div> <div>TYPE: UF</div> <div>FRAME: 48Y</div> <div>VOLTS: 208-230</div> <div>PH: 1</div> <div>AMPS: 1.0,0.9</div> <div>HZ: 60</div> <div>INS.: B</div> <div>AMB.: 40 °C</div> <div>DUTY: AIR OVER</div> <div>CAP.: 4 MFD/370V</div> <div>ENCL: SEMI-ENCL.</div> <div>UL LOGO</div> <div>CSA LOGO</div> <div>THERMALLY PROTECTED</div>				<div>EXTERNAL CONNECTION DIAGRAM</div> <div></div> <div>614131-002</div>																					
<div>PERFORMANCE CURVE NO.</div> <div>C32681</div>		<div>TORQUE @ 1075 RPM (25°C)</div> <div>13.3 OZ. FT.</div>		<div>APPROVED SAMPLE</div> <div>0603136C</div>		<div>UL COMPONENT</div> <div>FILE # CCN # FILE # CLASS #</div> <div>E46412 PRGY2 LR43341 4211-01</div>																			
				<div>LEAD DATA</div> <table><tr><td>GREEN/YELLOW (GRD)</td><td>11.0/13.0 [279/330]</td><td>#10 EYELET</td></tr><tr><td>BROWN</td><td>14.0/16.0 [356/406]</td><td>.25[6.4] FLAG</td></tr><tr><td>RED</td><td>14.0/16.0 [356/406]</td><td>.25[6.4] FLAG</td></tr><tr><td>BLACK</td><td>18.0/20.0 [457/508]</td><td>.25[6.4] FLAG</td></tr><tr><td>WHITE</td><td>14.0/16.0 [356/406]</td><td>.25[6.4] FLAG</td></tr><tr><td>COLOR</td><td>LENGTH</td><td>TERMINAL OR STRIP LENGTH</td></tr></table>		GREEN/YELLOW (GRD)	11.0/13.0 [279/330]	#10 EYELET	BROWN	14.0/16.0 [356/406]	.25[6.4] FLAG	RED	14.0/16.0 [356/406]	.25[6.4] FLAG	BLACK	18.0/20.0 [457/508]	.25[6.4] FLAG	WHITE	14.0/16.0 [356/406]	.25[6.4] FLAG	COLOR	LENGTH	TERMINAL OR STRIP LENGTH		
GREEN/YELLOW (GRD)	11.0/13.0 [279/330]	#10 EYELET																							
BROWN	14.0/16.0 [356/406]	.25[6.4] FLAG																							
RED	14.0/16.0 [356/406]	.25[6.4] FLAG																							
BLACK	18.0/20.0 [457/508]	.25[6.4] FLAG																							
WHITE	14.0/16.0 [356/406]	.25[6.4] FLAG																							
COLOR	LENGTH	TERMINAL OR STRIP LENGTH																							
				<div>ENCLOSURE</div> <table><tr><td>MAIN FRAME - OLE</td><td>ENCLOSED WITH DRAIN HOLE</td></tr><tr><td>END FRAME - OLE</td><td>OPEN</td></tr><tr><td>MAIN FRAME - LE</td><td>ENCLOSED WITH DRAIN HOLE</td></tr><tr><td>END FRAME - LE</td><td>OPEN</td></tr></table> <div>CUSTOMER DISTRIBUTION SERVICE</div>		MAIN FRAME - OLE	ENCLOSED WITH DRAIN HOLE	END FRAME - OLE	OPEN	MAIN FRAME - LE	ENCLOSED WITH DRAIN HOLE	END FRAME - LE	OPEN												
MAIN FRAME - OLE	ENCLOSED WITH DRAIN HOLE																								
END FRAME - OLE	OPEN																								
MAIN FRAME - LE	ENCLOSED WITH DRAIN HOLE																								
END FRAME - LE	OPEN																								
<div>GEOMETRIC CHARACTERISTICS &amp; SYMBOLS</div> <div>≡ FLATNESS</div> <div>— STRAIGHTNESS</div> <div>∠ ANGULARITY</div> <div>⊥ PERPENDICULARITY (SQUARENESS)</div> <div>// PARALLELISM</div> <div>○ ROUNDNESS (CIRCULARITY)</div> <div>⌀ CYLINDRICITY</div> <div>△ PROFILE OF ANY SURFACE</div> <div>∧ PROFILE OF ANY LINE</div> <div>↗ RUNOUT</div> <div>⊕ TRUE POSITION</div> <div>◎ CONCENTRICITY</div> <div>≡ SYMMETRY</div> <div>ASME Y14.5M 1994</div>		<div>REGAL-BELOIT CORPORATION (RBC) PROVIDES TECHNICAL ASSISTANCE TO OUR CUSTOMERS IN SEVERAL AREAS. SINCE RBC DOES NOT RECEIVE ALL DATA CONCERNING THE USE AND APPLICATION OF THE MOTOR, THE SUITABILITY OF THE MOTOR FOR THE APPLICATION MUST BE DETERMINED BY THE CUSTOMER.</div> <div>DIMENSIONS WITHOUT TOLERANCES ARE FOR REFERENCE ONLY.</div>		<div>DR BY: AMY</div> <div>04-23-2007</div> <div>APPD:</div> <div>THIRD ANGLE PROJECTION</div> <div>EDS DATE 02-22-2008</div> <div>FORMAT REV G</div> <div>CONFIDENTIAL: THIS DRAWING AND ITS INFORMATION ARE THE EXCLUSIVE AND CONFIDENTIAL PROPERTY OF REGAL-BELOIT CORPORATION AND ARE NOT TO BE DISCLOSED, DUPLICATED, DISTRIBUTED OR OTHERWISE USED WITHOUT THE WRITTEN CONSENT OF REGAL-BELOIT CORPORATION. -ALL RIGHTS RESERVED.</div>		<div></div> <div>DESCRIPTION</div> <div>MODEL-RFHP-48FR</div> <div>OUTLINE</div> <div>SIZE C</div> <div>DWG NO F48Y98A01</div> <div>SCALE NONE</div> <div>SHEET 1</div>																			



