



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 193427 CUST PN: B238V1 HP: SF: ROT: CW RPM: 3450/1725 TYPE: CXP M CODE: D FORM: KHM FRAME: R56Y VOLTS: 230 AMPS: 16.4 MAX AMPS: SF AMPS: PH: 1 HZ: 60 INS: B AMB: 50 DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		1.SHAFT RUNNOUT NOT TO EXTEND .002[.05] T.I.R.

PERFORMANCE CURVE	APPROVED SAMPLE		
19228311	-		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER	DISTRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
A	A. BAUGHMAN	02-11-2015	DEC. INCH mm ANGLE
ECO	APPROVED BY	DATE	.XX \pm 0.02 [12.5] \pm 0.5
ECO-0071558	A. BAUGHMAN	02-11-2015	.XXX \pm 0.005 [12.7] \pm 0.127
NEW			.XXXX \pm 0.0005 [12.7] \pm 0.0127

REMOVE BURRS & BREAK SHARP EDGES .003/015 [0.076/381]
 CORNER FILLETS .02 [1.51]
 MACHINED SURFACES $\frac{25}{\text{INCH}} \sqrt{\text{mm}} \frac{32}{\text{mm}}$
 mm SHOWN IN [BRACKETS]

DRAWN BY:	DATE:	APPROVED BY:	DATE:	THIRD ANGLE PROJECTION
A. BAUGHMAN	02-11-2015	A. BAUGHMAN	02-11-2015	
DESCRIPTION		MATERIAL		PROCESS/FINISH
MODEL-CFHP-56FR OUTLINE				
SIZE	DWG NO	SHEET		
C	B238V1	1		



Regal Beloit America, Inc.