



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 196263 CUST PN: B2748 HP: 2.0 SF: 1.3 ROT: CCWPE RPM: 3450 TYPE: CX CODE: G FORM: KJM FRAME: Y 56 Y VOLTS: 230 AMPS: - MAX AMPS: - SF AMPS: 11.5 PH: 1 HZ: 60 INS: F AMB: 50 °C DUTY: CONT ENCLOSURE: DP THERMALLY PROTECTED		<ol style="list-style-type: none"> <li>FOR THREADED SHAFT EXTENSION ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004[.10] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR.</li> <li>END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST.</li> <li>FINISH PAINT TO BE BLACK.</li> <li>REFERENCE MODEL: B748</li> </ol>

PERFORMANCE CURVE	APPROVED SAMPLE		
15593311	0601158		
UL COMPONENT	CSA		
PENDING	PENDING		
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER	DSITRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED	DRAWN BY:	REGAL™ Regal Beloit America, Inc.
H	G. RODRIGUEZ	04-24-2019	DEC. INCH mm ANGLE	BL	
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°	DATE:	
ECO-0165900	G. RODRIGUEZ	04-24-2019	.XXX ±0.02 [±0.51]	09-01-2009	
SEE ECO			.XXX ±0.005 [±0.127]	APPROVED BY:	
			.XXXX ±0.0005 [±0.0127]	SH	
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/.381]	DATE:	
			CORNER FILLETS .02 [51]	09-01-2009	
			MACHINED SURFACES $\sqrt{.125}$ INCH $\sqrt{3.2}$ mm	REFERENCE	
			mm SHOWN IN [BRACKETS]	MATERIAL	
				PROCESS/FINISH	
				THIRD ANGLE PROJECTION	
				SIZE DWG NO	
				C B2748	
				SHEET	
				1	