



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 196262 CUST PN: B2858 HP: 1.5 SF: 1.5 ROT: CCWPE RPM: 3450 TYPE: CX CODE: K FORM: FRAME: Y 56 Y VOLTS: 230/115 AMPS: - MAX AMPS: - SF AMPS: 10.5/21.0 PH: 1 HZ: 60 INS: F AMB: 50 C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		<ol style="list-style-type: none"> FOR THREADED SHAFT EXTENSION ECCENTRICITY OF THREADED PORTION OF SHAFT IS HELD WITHIN .004[.10] TOTAL GAGE READING WITH THE INDICATOR ON O.D. OF GROUND RING GAGE AS SHOWN. THE GAGE BEING STATIONARY WITH RESPECT TO THE ROTOR. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST. FINISH PAINT TO BE BLACK. REFERENCE MODEL: B858. CONNECTED FOR 230V. DUAL VOLTAGE MOTOR. SEE CONNECTION DIAGRAM TO CHANGE VOLTS TO 115V.

PERFORMANCE CURVE	APPROVED SAMPLE		
16387811	0601046		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
PENDING	PENDING	PENDING	PENDING
CUSTOMER	DISTRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
F	G. RODRIGUEZ	04-24-2019	DEC. INCH mm ANGLE
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°
ECO-0165900	G. RODRIGUEZ	04-24-2019	.XX ±0.02 [±0.51]
ECO DESCRIPTION			.XXX ±0.005 [±0.127]
SEE ECO			.XXXX ±0.0005 [±0.0127]
			REMOVE BURRS & BREAK SHARP EDGES .003/.015 [0.076/.381]
			CORNER FILLETS .02 [.51]
			MACHINED SURFACES $\frac{125}{\text{mm}}$ $\frac{3.2}{\text{INCH}}$
			mm SHOWN IN [BRACKETS]

DRAWN BY: AL	Regal Beloit America, Inc.
DATE: 11/16/2017	
APPROVED BY: TZ	DESCRIPTION: MODEL-CFHP-56FR OUTLINE
DATE: 11/16/2011	MATERIAL: _____ PROCESS/FINISH: _____
REFERENCE: _____	SIZE DWG NO: C B2858 SHEET: 1