



NAMEPLATE DATA	EXTERNAL CONNECTION DIAGRAM	NOTES
MODEL: 165125 CUST PN: B817 HP: 3.0 SF: 1.15 ROT: CCWPE RPM: 3450 TYPE: CX CODE: F FORM: - FRAME: Y 56 C VOLTS: 208-230 AMPS: SF 15.0-13.6 MAX AMPS: - SF AMPS: - PH: 1 HZ: 60 INS: B AMB: 50°C DUTY: CONT ENCLOSURE: ODP THERMALLY PROTECTED		1. PILOT DIAMETER IS CONCENTRIC WITH SHAFT CENTERLINE WITHIN .006[.15] T.I.R. 2. FACE OF MOUNTING FLANGE IS PERPENDICULAR TO SHAFT CENTERLINE WITHIN .004[.10] T.I.R. 3. SHAFT RUNOUT NOT TO EXCEED .002[.05] T.I.R. 4. END PLAY NOT TO EXCEED .010[.25] MEASURED WITH NO THRUST. 5. FINISH PAINT TO BE BLACK.

PERFORMANCE CURVE	APPROVED SAMPLE		
15530411	-		
UL COMPONENT	CSA		
FILE#	CCN#	FILE#	GUIDE#
E14663	XZWR2	LR4642	4211-01
CUSTOMER	DISTRIBUTION		

DRAWING REVISION	REVISION BY	DATE	TOLERANCES UNLESS OTHERWISE SPECIFIED
F	G. RODRIGUEZ	04-25-2019	DEC. INCH mm ANGLE
ECO	APPROVED BY	DATE	.XX ±0.1 [±2.5] ±0.5°
ECO-0165900	G. RODRIGUEZ	04-25-2019	.XX ±0.02 [±0.51]
ECO DESCRIPTION			.XXX ±0.005 [±0.127]
SEE ECO			.XXXX ±0.0005 [±0.0127]

DRAWN BY:	DATE:
AS	10-21-2010
APPROVED BY:	DATE:
TZ	10-21-2010
REFERENCE	THIRD ANGLE PROJECTION
	AS SHOWN

REGAL™	Regal Beloit America, Inc.
DESCRIPTION: MODEL-CFHP-56FR	
MATERIAL:	PROCESS/FINISH:
SIZE DWG NO: C	OUTLINE
SHEET: 1	